

## PSSO K-315HD 3-Way Top 1000W

PRO PA speaker, 15" woofer, 6.5" mid, 1.4" horn, 1000 W RMS (Biamp)

Réf. : 11041112

GTIN: 4026397483079



**L'article n'est plus disponible.**

### Caractéristiques:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Biamp operation
- Housing made of 15 mm/18 mm birch plywood
- 38 cm neodymium bass speaker (15") and 16.5 cm midrange speaker (6.5") with diecast aluminum basket
- 36 mm neodymium hybrid horn tweeter (1.4") with 72 mm voice coil (2.8")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, on a subwoofer or speaker stand, suspended
- Pilote de CELTO ACOUSTIQUE
- Développé en Europe

### Logistique

EAN / GTIN: 4026397483079

Poids: 40,70 kg

Longueur: 0.56 m

Largeur: 0.55 m

Hauteur: 0.92 m

Article encombrant

### Données techniques:

Capacité de charge:	Programme: 1400W Nominale: 700W RMS
Plage de fréquence:	45 - 20000 Hz
Sensibilité:	108 dB MHF; 98 dB LF
Pression acoustique max.:	137 dB

Impédance:	4/8 Ohm Biamp
Connexions:	Entrée: Enceinte via 2 x Boîtier d'enceinte encastrable (F)
Fréquence de rupture:	2500 Hz 500 Hz
Enceinte:	1 x Boumeur 15"
Type d'enceinte:	Boîtier compact
Utilisation de la marque:	Pilote de CELTO ACOUSTIQUE
Dimension:	Largeur : 45 cm Profondeur : 44,3 cm Hauteur : 80 cm
Poids:	36,75 kg
	300 W RMS MHF
Components:	38 cm woofer (15"), 16.5 cm driver (6.5"), 3.6 cm horn tweeter (1.4")
Connection:	2 x Speakon
Impedance:	
LF:	8 ohms
MHF:	8 ohms
Dispersion angle:	70° x 40° above 600 Hz