



Caractéristiques:

- Rugged full-range PA top speaker, qualified for suspension and clubs
- Housing made of 18 mm (13 layers) birch plywood
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 30 cm neodymium bass speaker (12") with diecast aluminum basket
- 36 mm neodymium driver (1.4"), 72 mm voice coil (2.8")
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Movable mounting bracket for ceiling or wall installation
- Scratch-resistant lacquer surface
- Applications: standing, on a subwoofer or suspended
- Pilote de CELTO ACOUSTIQUE
- Développé en europe

Logistique

EAN / GTIN: 4026397494013
Poids: 17,00 kg
Longueur: 0.48 m
Largeur: 0.48 m
Hauteur: 0.49 m

Données techniques:

| | |
|---------------------------|---------------------------------------|
| Capacité de charge: | Programme: 800W Nominale: 400W RMS |
| Plage de fréquence: | 59 - 21000 Hz |
| Sensibilité: | 100 dB |
| Pression acoustique max.: | 132 dB |
| Dispersion: | 70° x 70° |

| | |
|---------------------------|---|
| Impédance: | 8 Ohm |
| Connexions: | Entrée: Enceinte via 2 x SpeakON 4 broches version encastrable (F) |
| Fréquence de rupture: | 1400 Hz |
| Enceinte: | 1 x Boumeur 12" 1 x Pavillon 1,5" Bobine mobile graves 3" Ouverture du raccordement du pavillon 1,35" Pilote de compression à bobine mobile aiguës 3" |
| Type d'enceinte: | Enceinte coaxiale; boîtier compact |
| Utilisation de la marque: | Pilote de CELTO ACOUSTIQUE |
| Dimension: | Largeur : 38 cm Profondeur : 38 cm Hauteur : 38 cm |
| Poids: | 14,80 kg |

Contenu de la livraison:
