OMNITRONIC HM-105 Wireless Microphone WAMS-05

Réf. : 13055098

GTIN: 4026397282696

High-quality hand-held microphone for WAMS-05

L'article n'est plus disponible.

Description:

The HM-105 is a dynamic hand-held microphone with PLL multifrequency transmitter which serves for wireless transmission of speech and vocals to the receiving unit RM-105 of the PA system W.A.M.S.-05. The microphone operates in the range of 863.100 - 864.900 MHz. The frequency range is divided into 16 channels, which can be selected as desired. The unit is tuned to the frequencies of the receiver module.

Logistique

EAN / GTIN: 4026397282696
Poids: 0,32 kg
Longueur: 0.28 m
Largeur: 0.07 m
Hauteur: 0.06 m

Caractéristiques:

- Integrated multifrequency transmitter with UHF PLL technology, suitable for W.A.M.S.-05 system
- Dynamic microphone capsule
- Cardiodid characteristic
- Operation in the low-interference UHF-band (863.1-864.9 MHz) with 16 frequencies selectable
- LCD for channel, frequency and battery capacity
- Transmitting power 10 mW
- Sensitivity adjustable in 2 steps
- Mute function
- For 2 x 1.5 V mignon batteries or 2 x 1.2 V rechargeable batteries (type AA) (not included)
- With charging port, suitable for optional charger HM-105
- Delivery incl. 4 color caps
- License-free and approved in the EU
- UHF 863-865 MHz sans inscription et sans frais en Europe

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

Données techniques:

Type:	Émetteur à main
Branchement électrique:	Pile/batterie
Type de micro:	Dynamique
Batterie:	2 x 1,5 V AA Mignon LR06 alcaline au manganèse ci-joint
Plage de fréquence:	70 - 16000 Hz
Bande de fréquences:	UHF 863-865 MHz
Dimension:	Longueur : 26 cm Diamètre : Ø 4 cm
Poids:	260 g
Carrier frequency:	UHF 863.100-864.900 MHz
Frequency stability:	±0.005 %
RF power output:	10 mW
Polar pattern:	Omnidirectional
Range:	approx. 30 m
Power supply:	2 x 1.5 V mignon batteries (type AA)/
	2 x 1.2 V rechargeable batteries (type AA)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.