

OMNITRONIC UHF-202 Wireless Microphone System 830.9+824.925MHz

Système de microphone 2 canaux, technologie UHF-PLL

Réf. : 13063235

GTIN: 4026397533620



L'article n'est plus disponible.

Caractéristiques:

- 2-channel receiver unit and 2 hand-held microphones with UHF PLL technology
- Operation in the Duplex Gap with 830.900 and 824.925 MHz
- Parallel operation of up to 4 transmission channels is possible without any interference
- 2 separate channels with volume controls and LEDs for carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Jack cable included
- Microphones with mute switch and color caps for distinction on stage
- Matching pocket transmitters can be ordered separately
- License-free in Germany and 13 other EU countries

L'étendue des fournitures

- 1 x microphone

Logistique

EAN / GTIN: 4026397533620

Poids: 1,35 kg

Longueur: 0.41 m

Largeur: 0.34 m

Hauteur: 0.07 m

Données techniques:

Plage de fréquence: 40 - 18000 Hz

Dimension: Largeur : 21 cm
Profondeur : 15,5 cm
Hauteur : 4,5 cm

Microphone

Batterie: 4 x Mignon (AA) (non incluse dans la livraison)

System: Non-diversity, 2 channels

| | |
|---------------------|--|
| Carrier frequency: | 830.900 MHz, 824.925 MHz |
| Coverage: | 50 m (with line-of-sight) |
| RF power output: | 10 mW |
| Modulation method: | F3E |
| S/N ratio: | >105 dB |
| Selectivity: | >80 dB |
| T.H.D.: | <0.5 % at 1 kHz |
| Audio outputs: | 400 mV, 2.2 kohms (XLR, bal.) |
| | 200 mV, 2.2 kohms (6.3 mm jack, unbal.) |
| Power supply: | |
| Receiver: | 100-240 V AC, 50/60 Hz via supplied power unit |
| Power consumption: | 10 W |
| Dimensions, weight: | |
| Receiver: | 155 x 210 x 45 mm (L x W x H), 455 g |
| Microphones: | 50 x 265 mm (D x L), 175 g |