

OMNITRONIC WM-2402 Wireless mic system

Système de microphone numérique sans fil 2 canaux, 2,4 GHz

Réf. : 13072002

GTIN: 4026397462517



Caractéristiques:

- Wireless microphone system includes receiver unit and 2 hand-held microphones with integrated PLL transmitter
 - Digital transmission in the 2.4 GHz range provides for high resistance to interference and unique sound quality
 - 2 channels with separate level control
 - 16 frequencies (2,404-2,476 MHz) for each channel can be selected at the transmitter
 - 2 systems can be used simultaneously (corresponds to 4 microphone transmission paths)
 - 6.3 mm output for mixed signal
 - Supercardioid microphone cartridges
 - Incl. power unit and jack cable
 - License-free and approved in the EU
- microphone**
- Possibilité de fonctionnement sur batterie/piles

Logistique

EAN / GTIN: 4026397462517

Poids: 1,45 kg

Longueur: 0.34 m

Largeur: 0.28 m

Hauteur: 0.07 m

Données techniques:

Alimentation électrique: 100-240 V CA, 50/60 Hz

Puissance totale de raccordement: 7,50 W

Plage de fréquence: 50 - 15000 Hz

Dimension: Largeur : 22 cm
Profondeur : 4,4 cm
Hauteur : 13,3 cm

| | |
|-----------------------|---|
| Batterie: | 4 x 1,5 V AA Mignon LR06 alcaline au manganèse ci-joint |
| Carrier frequency: | 2404-2476 MHz, 16 channels |
| RF power output: | 10 mW |
| Coverage: | 20 m (in buildings), 30 m (in the open air) |
| THD: | <1 % |
| Dynamic range: | 87 dB |
| Microphone cartridge: | dynamic |
| directivity: | supercardioid |
| Impedance: | 600 ohms |
| Audio output: | 6.3 mm jack, unbal., 100 mV |
| Receiver: | 100-240 V AC, 50/60 Hz |
| | via supplied power unit |
| Dimensions, weight | |
| Receiver: | 220 x 44 x 133 mm, 550 g |
| Microphone: | 55 x 260 mm, 120 g |

Contenu de la livraison:

1 x microphone