



Caractéristiques:

EUROLITE DF-40 LED display 92x92

Ultra flat and flexible LED display

- Ultraflat and flexible LED display for bright and colorful projection of videos and graphics
- Bends, rolls and moulds around almost any shape for waves, columns, circles, arcs and angles
- 4 millimeters thin and 800 grams light for convenient transport and simple installation
- 40 mm pixel pitch (seamless image at about 40 m)
- Applicable for installation in counters, columns and rear walls in shops and clubs, on fairs and various other environments
- Extendable for of large video billboards
- Control per network protocol in live mode with PC software or in stand-alone mode with media player (accessories)
- Control also possible per MADRIX, DMX and Artnet
- Large operating range from -20° to +50° C
- 484 LED 3in1 R/G/B (mélange de couleurs homogène)
- Commandé via DMX

EUROLITE DF Control system

Control unit for DF-40 LED display

- Control unit and PC software for controlling DF-40 LED displays
- Operation with the handy media player (80503610) or a network-compatible computer
- Create stunning light shows for your displays with the included light effect software
- Load your shows onto the included SD memory card for playback on the media player
- Ethernet input and output, LAN cable included

Logistique

EUROLITE DF power unit

Mountable power unit for DF-40 LED displays

- Power unit in aluminum housing for DF-40 LED displays
- Each DF-40 LED display requires a separate power unit
- Screw terminals
- Short-circuit proof, overload-protected
- Protected against excess temperature

EUROLITE DF Media player

Media player for DF-40 LED display

- Media player and control software for flexible use DF-40 LED displays
- Allows to run light shows and videos on your displays without the need for a computer
- Use your PC to create stunning light shows with the included light effect software
- Load your shows onto the included SD memory card for playback on the media player
- Four operating buttons for setting brightness, speed, color and playback mode
- 6 cm backlit display
- Ethernet connectors, LAN cable included

Données techniques:

Poids: 6,45 kg

EUROLITE DF-40 LED display 92x92

Puissance totale de raccordement:	40,00 W
Type de LED:	484 x 3in1 R/G/B (mélange de couleurs homogène)
Commande:	DMX
Dimension:	Largeur : 92,5 cm Profondeur : 4 cm Hauteur : 92 cm
Poids:	0,60 kg
Resolution:	22 x 22 pixels
Pixel pitch:	40 mm
Pixel configuration:	tricolor RGB LEDs
Display mode:	synchronous to PC, or asynchronous per media player
Brightness:	R 250-1000 mcd, G 500-1650 mcd, B 80-500 mcd
Viewing angle:	120°
Data refresh rate:	400 cycles/sec
Colors:	16.7 million (R 256, G 256, B 256)
Operating temperature:	-20° to 50°C
Dimensions (L x W x H):	925 x 920 x 4 mm
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

EUROLITE DF Control system

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	10,00 W
Dimension:	Largeur : 16 cm Profondeur : 15,5 cm Hauteur : 5 cm
Poids:	1,10 kg
Signal input:	RJ45, CAT5e
Signal link:	RJ45, CAT5e
Number of displays:	max. 6 per control unit
Serial connection:	max. 255 control units for PC operation max. 48 control units for media player operation
Pixels:	max. 3072
Dimensions (L x W x H):	160 x 155 x 50 mm
System requirements:	Windows XP, Vista or 7 Separate network card (100 Mbps) SD card reader

EUROLITE DF power unit

Alimentation électrique:	100-240 V CA, 50/60 Hz
Dimension:	Largeur : 23 cm Profondeur : 15,5 cm Hauteur : 5 cm
Poids:	0,90 kg
Output voltage:	5 V DC
Output current:	40 A
Dimensions (L x W x H):	230 x 155 x 50 mm

EUROLITE DF Media player

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	10,00 W
Dimension:	Largeur : 19 cm Profondeur : 14 cm Hauteur : 4 cm
Poids:	0,85 kg
Signal output:	2 x RJ45, CAT5e
Storage medium:	SD memory card up to 2 GB (incl.)
Number of displays:	288 max.
Dimensions (L x W x H):	190 x 140 x 40 mm
System requirements:	Windows XP, Vista or 7 Separate network card (100 Mbps)

SD card reader

Contenu de la livraison:
