

## OMNITRONIC Set CMX-2000 + 2x DD-5220L

Set with digital DJ mixer/controller and two turntables

Réf. : 2000395

GTIN:



### Caractéristiques:

- 2-channel DJ mixer/MIDI controller bundled with Virtual DJ
- Optimized layout for Virtual DJ and Traktor PRO 2 - Virtual DJ 7 LE voucher included
- Traktor PRO 2 and Serato Scratch Live mappings available with full support for scratch and sample decks
- Flexibly combines stand-alone mixing of analog sources with MIDI control for DJ software
- Built-in DVS audio system for direct use of timecode systems with vinyl or CD in Virtual DJ and other open applications via USB
- 2 input channels with routing facility for analog inputs and MIDI decks as desired
- Full-fledged MIDI sections with 2 layers for 4-deck control
- Perfect MIDI control for file browsing, transportation, hot cues, samples, sample recorder, loops, effects, pitch und video transitions
- Advanced setup options for scratch DJs: crossfader and channel faders with adjustable curve and reverse selectors
- Built-in USB sound card 4 IN/4 OUT
- Supports Mac OSX, Windows XP, Vista, 7
- Professional-grade metal chassis with replaceable crossfader (45 mm)
- 2 line and 2 line/phono RCA inputs for connecting CD players, turntables and other external hardware
- 2 AUX inputs (3.5 mm/6.3 mm jack) connect MP3 players and tablets
- Mic input (XLR/6.3 mm jack) with tone control and talkover
- 2 master outputs (XLR/RCA) for PA applications
- Booth output (RCA), independently adjustable
- 3.5 mm/6.3 mm jack dual headphones output with cue mix control
- Bright color-coded LED buttons provide optimal visual feedback while triggering loops, samples, effects and cue points
- User-definable LED modes for Serato Scratch Live

### Logistique

- Dual-function audio/video crossfader for video performances within Virtual DJ
- 3-band EQ (high, mid, low) and HP/LP filter per channel
- Mixer section switchable between analog mode and MIDI mode
- File selector encoder and 2 load buttons for mouseless music library control
- 8 Hot Cue buttons per channel
- Auto Loop function with Beat Jump (Loop Cut), manual Loop In/Out buttons
- FX/sampler units with 4 parameter controls and 4 buttons per channel
- Various controls for GUI, mixer and video
- Shift button for various dual-button operations
- Separate VU meters for master and PFL signal
- Crossfader with faderstart function for compatible CD players
- Compatible to any MIDI-controlled DJ software including Serato Scratch Live, Traktor, Ableton Live
- All MIDI control elements can be edited and freely assigned
- ASIO drivers with minimum latency and high-quality audio characteristics available for download (PC)
- L'appareil peut être connecté au PC via USB, Connecté à Virtual DJ compatible midi
- <p>OMNITRONIC Platine DD-5220L noire et blanche
- <h2 class="featureSatz">Platine de DJ « Ultra Torque » et commutateur phono/ligne</h2>Direct drive high-torque motor Quartz-controlled for highest speed precision
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control  $\pm 10\%$ ,  $\pm 20\%$ ,  $\pm 50\%$
- Selectable quartz-controlled pitch lock
- Quick start
- Adjustable start/stop time
- 2 large start/pause buttons
- Reverse run
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing and adjustable feet
- Switchable phono/line output
- Extremely resonance-free due to optimally combined components
- Platter and motor are directly connected for highest stability
- Recessed connections for easy case mounting
- Delivery includes headshell, slipmat and RCA cable
- Dust cover and pick-up system optionally available
- Réglage du niveau:  $\pm 10\%$ ,  $\pm 20\%$ ,  $\pm 50\%$

## Données techniques:

---

Poids: 26,50 kg

---

### OMNITRONIC CMX-2000 2+1-channel MIDI controller

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	14 W
Branchement électrique:	Alimentation électrique via appareils froids (M) version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison)  Tramite
Port USB:	USB 2.0, type B
PC connect:	Virtual DJ via USB Compatible midi
Dimension:	Largeur : 36 cm Profondeur : 26,5 cm Hauteur : 10,5 cm

---

Poids:	3,90 kg
Inputs:	
Line:	2 x stereo RCA
Line/phono:	2 x stereo RCA, switchable
DJ microphone:	combination XLR/6.3 mm jack, bal.
Aux:	3.5 mm jack and stereo RCA
Outputs:	
Master:	XLR L/R and stereo RCA
Booth:	stereo RCA
Headphones output:	3.5 mm and 6.3 mm jack
Converter:	16 bits
Sample rate:	48 kHz
Faderstart:	2 x 3.5 mm jack

### OMNITRONIC Platine DD-5220L noire et blanche

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	15,00 W
Classe de protection:	SK I
Branchement électrique:	Fixe câble d'alimentation à prise euro Tramite
Plage de fréquence:	20 - 20000 Hz
Type d'entraînement:	Entraînement direct piloté par quartz Moteur à courant continu sans balais
Transmission:	Couple de démarrage: 4,5 kg/cm Durée de démarrage: 0,2 - 6 sec., réglable Durée de décélération: 0,2 - 6 sec., réglable Transition de la vitesse de rotation: <1s 1kHz 5cm/sec
Pleurage et scintillement:	<0,1 % WRMS
Grondement:	60 dB DIN B
Vitesse de rotation:	33 tr/min; 45 tr/min; 78 tr/min avant/arrière
Bras de lecture:	En forme de S avec une suspension à cardan Longueur : 230 Hauteur de bras de lecture : 8 - 10,5 mm réglable Surplomb : 15 mm Force d'appui : 0-4 g, réglable
Niveau de sortie:	Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec Line 90-216 mV/ 1 kHz 5 cm/sec
Connexions:	Sortie: Line/Phono via 1 x RCA stéréo
Réglage du niveau:	±10%, ±20%, ±50%
Dimension:	Largeur : 45 cm Profondeur : 35,3 cm Hauteur : 15,6 cm
Poids:	11,30 kg
Matériau:	Métal
Dimension:	Diamètre : Ø 33,2 cm

Poids:

1,425 kg

---

**Contenu de la livraison:**

---

- 1 x Appareil
- 1 x Câble secteur/câble d'alimentation
- 1 x Platine
- 1 x Matelas en feutre
- 1 x shellset
- 1 x Contre-poids
- 1 x prise
- 1 x adaptateur
- 1 x câble RCA
- 1 x Mode d'emploi