

**NEUTRIK RCA plug Pro NF2CB 2x**  
PRO RCA plugRéf. : 30204050  
GTIN: 7613187001109**L'article n'est plus disponible.****Caractéristiques:**

- Professional RCA plug with gold plated contacts and spring loaded ground contact
- Direct electrical connection from ground contact to the signaling path
- Easy assembly and soldering (large soldering area, rapid-flow plating)

**Logistique**EAN / GTIN: 7613187001109  
Poids: 0,05 kg  
Longueur: 0.14 m  
Largeur: 0.10 m  
Hauteur: 0.01 m**Données techniques:**

Rated current:	16 A
Rated voltage:	50 V ac
Insulation resistance:	>100 Gohms
Dielectric strength:	1500 V DC
Capacitance (pin to shell):	7 pF
Cable anchoring:	Neutrik chuck principle
Cable OD range:	3.0-5.5 mm (blue chuck) and 5.5-7.3 mm (black chuck)
Max. wire size:	2.5 mm <sup>2</sup> / 14 AWG
Solderability:	complies with IEC 68-2-20
Shell:	Brass CuZn39Pb3 black coated
Contact pin:	Brass CuZn39Pb3 0.5 mm Au plated
Ground contact:	Brass CuZn39Pb3 0.5 µm Au plated over 5 µm Ni

Chuck:	Polyacetal POM
Insulator:	PBTP
Temperature range:	-30°C to +80°C