
SOMMER CABLE DMX cable XLR 5pin 20m gy Hicon

Câble de données de haute qualité

Réf. : 3030746UGTIN: 4049371022620

**L'article n'est plus disponible.****Description:**

DMX cable by premium manufacturer Sommer Cable

These premade cables are the perfect choice for the transmission of the 110 ohms AES/EBU DMX512 data format.

Important note: the use of a standard microphone cable is not recommended due to data and information losses (caused by the skin effect). In the lighting domain data losses cause a total jam with signal transmissions or the control of scanner systems.

The very affordable price of this cable should make it easy to switch from a standard microphone cable to a proper AES/EBU cable. Our AES/EBU cable guarantees the error-free data transfer even over longer distances of up to 100 metres. We use the BINARY 434 AES/EBU MKII AES/EBU cable with 100 % shielding and the HICON XLR connectors.

Logistique

EAN / GTIN: 4049371022620

Poids: 1,41 kg

Longueur: 0.28 m

Largeur: 0.31 m

Hauteur: 0.05 m

Caractéristiques:

- AES/EBU- and DMX-conformant, highly flexible
- Very good shielding through the use of copper spiral shielding and a fleece vaporized with aluminum
- Extremely robust with an especially strong jacket
- Only a little more expensive than a standard microphone cable
- For networking of scanners, lighting units, digital mixing boards, etc.
- For indoor and outdoor installation
- For connection of digital audio amplifiers, DAT-recorders, etc.

Données techniques:

Longueur du câble: 20 m

Raccord A:	1 x XLR (M) 5 broches
Raccord B:	1 x XLR (F) 5 broches
Couleur:	Gris