

## EUROLITE ML-300 ABL Spot

Projecteur de taille moyenne à ampoule halogène et éclairage d'ambiance LED

Réf. : 41600005

GTIN: 4026397655513



## L'article n'est plus disponible.

### Description:

Effect spotlight with halogen lamp and LED ambient lighting

Use this effect spotlight on stages, events or presentations to achieve decorative light and show effects.

The EUROLITE ML-300 ABL Spot is a medium-sized spotlight with halogen lamp and LED ambient lighting. Under the grille cover, LEDs in red, green and blue are hidden to completely illuminate the large reflector. A 300 W GY 9.5 lamp, which is not included in the scope of delivery, is used in the middle.

When dimmed, the halogen lamp produces a wonderfully golden atmospheric light, but when fully extended it produces a bright, dazzling light.

Adjust the strobe effect speed and the dimmer brightness comfortably via DMX - also different dimmer curves are selectable. The strobe effect scores with 20 flashes per second. You can select 35 colors directly.

The spotlight is controlled via DMX, with master/slave function, in stand-alone mode or with the infrared remote control included in the scope of delivery. Addressing and settings can be made easily using the integrated control unit with LCD and the three control buttons.

With the Neutrik PowerCon mains connection and loop-through output, you can supply up to six devices with power.

### Logistique

EAN / GTIN: 4026397655513

Poids: 8,25 kg

Longueur: 0.45 m

Largeur: 0.48 m

Hauteur: 0.43 m

## Caractéristiques:

---

- RGB LEDs are concealed under the mesh cover, in order to completely illuminate the large reflector with color
  - When dimmed, the halogen lamp produces a wonderful, golden atmosphere light; when fully illuminated a bright, dazzling light
  - Strobe effect with adjustable speed
  - Various dimmer curves adjustable
  - Mains input and output for power linking up to 8 units
  - 18 LED puissantes 0,2 W SMD 5050 3in1 TCL RGB
  - Choix de couleur direct pour 35 couleurs
  - L'appareil est refroidi par refroidissement par convection passive
  - Commandé via stand-alone; Télécommande infrarouge; DMX
  - Déjà préprogrammé pour %: Light´J; LED PC-Control 512; Light Captain
  - Avec Étrier
  - Écran LCD
- L'étendue des fournitures**
- 1 x projecteur, 1 x mode d'emploi, 1 x câble secteur/câble d'alimentation, 1 x télécommande, 1 x batterie

## Données techniques:

---

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	315 W
Type de protection:	IP20
Source lumineuse appropriée:	230 V/300 W G-9,5
Tension nominale:	300 W
Branchement électrique:	Alimentation électrique via PowerCON (bleu), version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Sortie de courant:	PowerCON (gris)
Culot/douille:	GY9,5
Type de lampe:	Lampe halogène
LED:	18 x 0,2 W SMD 5050 3in1 TCL RGB
Fréquence du flash:	0 - 20 Hz
Canaux DMX:	1; 2; 4; 7
Entrée DMX:	1 x XLR (M) 3 broches version encastrable 1 x XLR (M) 5 broches version encastrée
Sortie DMX:	1 x XLR (F) 3 broches version encastrable 1 x XLR (F) 5 broches version encastrée
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; Télécommande infrarouge; DMX
Préprogrammé dans:	Light´J; LED PC-Control 512; Light Captain
Couleur du boîtier:	Argenté
Système d'enregistrement:	Étrier
Type d'écran:	Écran LCD
Dimension:	Largeur : 53 cm Profondeur : 27,5 cm Hauteur : 45,5 cm
Poids:	7,15 kg
Spécifications juridiques	

---

Produit spécial: Non destiné à l'éclairage de la pièce dans les ménages

---

Utilisation: Éclairage pour effets de spectacle

---