

## LASERWORLD DS-2000RGB ShowNET (2021)

Laser de spectacle à diodes, interface réseau ShowNET et logiciel gratuit

Réf. : 51743282

GTIN: 7640144997182



**L'article n'est plus disponible.**

### Caractéristiques:

- Suitable for both beginners and professional users
- Upgrades of version 2021: new back plate with Interlock IN and THRU, Power IN and THRU, new push buttons for X/Y Invert and the other functions, revised key switch, faster galvos (40 kpps @8° ILDA) and 50° maximum deflection
- Multiple preset laser patterns included
- Integrated Scan Fail Safety
- Low-maintenance due to Sealed Housing Technology
- 2000 mW guaranteed power
- Graphics capable - 40 kpps@8° ILDA
- Max scan angle 45°
- Full color mixing - analog modulation
- Extremely sharp intense beams - 4mm beam diameter and low divergence of 1.1mrad
- Save safety settings direct to the laser and they apply in all modes
- Link multiple units with linking Power, DMX and ILDA
- Integrated ShowNET network interface with free laser control software included
- Start with your own professional laser show thanks to the intuitive Showeditor laser show software
- The Showcontroller software is supported as well and can be purchased additionally
- The integrated ShowNET allows for direct input through ILDA and LAN. Besides DMX, it is possible to trigger single frames via ArtNET. Custom frames and shows can be played back from an integrated SD card (included in delivery) - even in sound-to-light and stand-alone mode.
- L'appareil est refroidi par ventilateur
- Commandé via DMX; ILDA; stand-alone; Commande de la musique via Microphone

### L'étendue des fournitures

- 1 x laser, 1 x mode d'emploi, 1 x câble secteur/câble d'alimentation, 2 x clé, 1 x interlock, 2 x vis moletée, 4 x cale, 1 x sac

### Logistique

EAN / GTIN: 7640144997182

Poids: 5,90 kg

Longueur: 0.31 m

Largeur: 0.29 m

Hauteur: 0.21 m

## Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	45 W
Type de protection:	IP20
Branchement électrique:	Alimentation électrique via P-Con (bleu), version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Sortie de courant:	1 x P-Con (gris), version encastrable
Classe laser:	4
Couleur du laser:	R/G/B
Module laser:	Rouge (R) 500 mW 638 nm Vert (G) 500 mW 520 nm B bleu 1400 mW 450 nm
Refroidissement:	Ventilateur
Commande:	DMX; ILDA; stand-alone; Commande de la musique via Microphone
Couleur du boîtier:	Noir
Dimension:	Longueur : 21 cm Largeur : 17 cm Hauteur : 14,5 cm
Poids:	5,27 kg