

## EUROLITE TMH XB-200 Moving Head Beam

High performance beam for 200 W discharge lamp

Réf. : 51786800

GTIN: 4026397556438



**L'article n'est plus disponible.**

### Caractéristiques:

- Very narrow beam angle with 2°
- With electronic ballast
- Color wheel with 13 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 13 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- For OSD 5 Reflector 200 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller
- Déjà préprogrammé pour %: LED PC-Control 512

### Logistique

EAN / GTIN: 4026397556438

Poids: 14,55 kg

Longueur: 0.52 m

Largeur: 0.38 m

Hauteur: 0.38 m

## Données techniques:

|                           |  |
|---------------------------|--|
| Alimentation électrique:  | 100-240 V CA, 50/60 Hz                                   |
| Préprogrammé dans:        | LED PC-Control 512                                       |
| Dimension:                | Largeur : 31 cm<br>Profondeur : 25 cm<br>Hauteur : 38 cm |
| Power consumption:        | 250 W  |
| DMX channels:             | 16   |
| DMX connection:           | 3-pin XLR  |
| Flash-rate:               | 1-10 Hz  |
| Color-wheel:              | 13 dichroic filters plus open                            |
| Static gobo-wheel:        | 13 gobos and open  |
| Maximum PAN-movement:     | 540°   |
| Maximum TILT-movement:    | 270°   |
| Beam angle:               | 2°   |
| Dimensions (L x W x H):   | 250 x 310 x 380 mm                                       |
| Weight:                   | 12 kg  |
| Spécifications juridiques |  |
| Produit spécial:          | Non destiné à l'éclairage de la pièce dans les ménages   |
| Utilisation:              | Éclairage pour effets de spectacle                       |