

EUROLITE TMH XB-230 Moving-Head Beam

High performance beam for 230 W discharge lamp

Réf. : 51786820

GTIN: 4026397555974



L'article n'est plus disponible.

Caractéristiques:

- Very narrow beam angle with 3°
- With electronic ballast
- Color wheel with 14 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 17 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- For OSD 7 Reflector 230 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller
- Gobos
- Effet beam
- L'appareil est refroidi par ventilateur
- Commandé via DMX; stand-alone

Logistique

EAN / GTIN: 4026397555974

Poids: 21,60 kg

Longueur: 0.47 m

Largeur: 0.43 m

Hauteur: 0.62 m

- Déjà préprogrammé pour %: LED PC-Control 512
- Avec un Angle de départ de 3°

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	300 W
Type de protection:	IP20
Type de lampe:	Lampe à décharge
Équipement:	Gobos
Refroidissement:	Ventilateur
Commande:	DMX; stand-alone
Préprogrammé dans:	LED PC-Control 512
Angle de départ:	3°
Angle de départ (1/2 pic):	3°
Couleur du boîtier:	Noir
Dimension:	Largeur : 39,5 cm Profondeur : 32 cm Hauteur : 51 cm
Poids:	19,14 kg
DMX channels:	16
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	18 Hz
Color-wheel:	14 dichroic filters plus open
Static gobo-wheel:	17 gobos and open
Maximum PAN-movement:	540°
Maximum TILT-movement:	250°
Beam angle:	3°
Dimensions (L x W x H):	395 x 320 x 510 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle