FUTURELIGHT PRH-540-2 Pro-Rotating-Holder

Goodbye to immovability

Réf. : 51837615

GTIN: 4026397230024

L'article n'est plus disponible.

Description:

Get it movin'! Due to the PRH-540-2, classic lighting elements as smoke-machines or audience-blinders can perform up to two and a half turns. As a consequence, they can be used pretty variably. The light-effects are carried by a rotating plate. Despite of the turns, there should be no fear of cable spaghetti; because the blinders or smokers are connected directly beneath the plate. With this technology there are no problems with the transmission of DMX-signals.

Caractéristiques:

- Base with rotary plate for mounting smoke machines, lighting effects and much more
- Ideal for a wide range of applications: fairs and exibitions, sales promotion in movie theatres, theatres and discotheques
- A DMX output, separate power outlet and signal output for an external tilt motor allow for the application of a wide range of devices
- Applicable for 15 kg maximum tearing load or 10 kg maximum pressing load
- Soft rotation in both directions
- Exact positioning via 16 bit Pan movement resolution
- Automatic correction of the Pan position
- Control board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan-Reverse, Program, Reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- DMX control via every standard DMX controller

Logistique

EAN / GTIN: 4026397230024

Poids: 17,25 kg

Longueur: 0.50 m

Largeur: 0.48 m

Hauteur: 0.32 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Dimension:	Largeur : 36,5 cm Profondeur : 21 cm Hauteur : 42,5 cm
Power consumption:	1500 W
Max. power output (safety power outlet):	1450 W
Max. total current (safety power outlet):	6.3 A
DMX channels:	4
DMX connection:	3-pin XLR
Dimensions (L x W x H):	425 x 365 x 210 mm
Max. tearing load:	15 kg
Max. pressing load:	10 kg
Weight:	15 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.