

FUTURELIGHT PHP-575E Moving-PAR

PRO moving multi lens spotlight

Réf. : 51837860

GTIN: 4026397269352



L'article n'est plus disponible.

Description:

The principal task of the PHP-575 is to highlight an object, not for concerts but like a classic spot for illumination. Especially on exhibitions or fashion shows the glistening bright light causes excitement. Mobility is its major advantage. Imagine a car-show. Vehicles can be lighted directly or indirectly - a moving circle around the car with several spots, for example. There will even be no problems if positions are changed, as the PHP-575 can react by simply turning in the right direction. Once installed, this moving-head is ready for everything.

Logistique

EAN / GTIN: 4026397269352

Poids: 23,80 kg

Longueur: 0.75 m

Largeur: 0.47 m

Hauteur: 0.51 m

Caractéristiques:

- With electronic ballast
- Spot with 4 exchangeable lenses (VNSP, NSP, MFL and WFL)
- High-quality die-cast housing for highest stability
- With color filter frame
- Exact positioning via 16 bit Pan/Tilt movement resolution
- Control board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off
- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- For MSR 575/2 GX-9.5 lamp
- DMX control via every standard DMX controller

Données techniques:

| | |
|------------------------------------|--|
| Alimentation électrique: | 230 V AC, 50 Hz |
| Puissance totale de raccordement: | 690 W |
| Mouvement de basculement max.TILT: | 265° Positionnement |
| Mouvement de pivotement max. PAN: | 630° Positionnement |
| Canaux DMX: | 6 |
| Dimension: | Longueur : 37 cm |
| Beam angle: | |
| VNSP/NSP/MFL/WFL: | approx. 15/19/21 x 34/30 x 51° |
| DMX channels: | 6 |
| DMX connection: | 3-pin XLR |
| Maximum PAN-movement 630°: | in 2.5 s |
| Maximum TILT-movement 265°: | in 1.5 s |
| Length of base: | 370mm |
| Width of yoke: | 420 mm |
| Height (head horizontal): | 490 mm |
| Weight: | 19.5 kg |
| Spécifications juridiques | |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |