


FUTURELIGHT PHW-260 incl. bulb

Multifunctional Washlight

Réf. : 51838705

GTIN: 4026397220308



L'article n'est plus disponible.

Caractéristiques:

- DMX-controlled operation or stand-alone operation with Master/Slave function
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- CMY color mixing
- Color-wheel with additional 5 discrete dichroic filters plus white, 3200 K and 5600 K correction-filters, UV-filter
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Macro-function for combinations between CMY color mixing and color-wheel
- Frost-filter for softer beam
- Beam-shape effect: wide and flat beam can steplessly be rotated by 180°
- Strobe effect of 1-13 flash per sec.
- Control board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off
- Remotely switching of the lamp
- Built-in demo sequence
- Preprogrammed variable/random strobe and dimmer pulse effects
- Black-out while Head moving or color changing
- Remotely controllable speed of PAN /TILT movement for easy programming
- Remote reset function
- Silent fans cooling; remotely controllable speed of fans
- Motorized zoom

Logistique

EAN / GTIN: 4026397220308

Poids: 28,70 kg

Longueur: 0.60 m

Largeur: 0.47 m

Hauteur: 0.51 m

- Mechanic dimmer
- Exact positioning via 16 bit Pan/Tilt movement resolution
- DMX control via every standard DMX controller

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	485,00 W
DMX channels:	17
DMX connection:	3-pin XLR
Flash-rate:	13 Hz
Color-wheel:	5 dichroic filters plus white, CTO and CTB correction-filters, UV-filter
Length of base:	370 mm
Width of yoke:	420 mm
Height (head horizontal):	470 mm
Weight:	24 kg
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle