

FUTURELIGHT PLB-5R Moving-Head

High performance beam with Philips Platinum 5R lamp and the multifunctionality of Moving Heads

Réf. : 51838960

GTIN: 4026397437898



L'article n'est plus disponible.

Caractéristiques:

- Double lamp lifetime with half power input and smaller dimensions compared to a 575 W lamp
- Supports RDM (Remote Device Management)
- Very narrow illumination angle
- Light beam is centered and moved exactly
- Color-wheel with 9 different, dichroic color filters and white and additionally with CTO and CTB correction filters and UV filter
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- 11, 13 or 16 DMX channels selectable for numerous applications
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel with 8 rotating gobos plus open
- Slot-in gobo-system for exchanging gobos without tools
- With gobo-shake function
- Rotating 8-facet prism
- Macro-function for rotating gobos/rotating prism combinations
- Graphic LCD display
- Strobe effect with 1-13 flashes per second
- Random strobe effect
- Stepless frost-filter for fading the projections in or out
- Mechanic dimmer
- Exact positioning via 16 bit resolution: color-wheel, gobo indexing, dimmer and PAN/TILT movement
- Automatic position correction
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc.
- Control board with LCD display and touch keyboard for adjusting the DMX-starting address, PAN/TILT reverse, program, reset, lamp on/off, operating hours

Logistique

EAN / GTIN: 4026397437898

Poids: 18,70 kg

Longueur: 0.64 m

Largeur: 0.42 m

Hauteur: 0.45 m

- PAN-angle switchable between 630° and 540°
 - DMX-controlled operation or stand-alone operation with master/slave function
 - 7 built-in programs can be called up via DMX-controller
 - 56 preprogrammed scenes in Program Run for stand alone operation
 - Number of scenes in Program Run can be changed individually
 - The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
 - Software upload by optional accessory via DMX link
 - Sound-controlled via built-in microphone
 - With PHILIPS MSD Platinum 5R discharge lamp
 - The integral mounting plate on the bottom of the device enables a permanent installation even without omega clamps, e.g. on the ceiling
 - Power connection via Neutrik PowerCon jack and included power cable
 - DMX-control via every standard DMX-controller
- Appareil**
- Sans fil, flexible et polyvalent
- L'étendue des fournitures**
- 1 x appareil

Données techniques:

| | |
|-------------------------------------|--|
| Alimentation électrique: | 230 V AC, 50 Hz |
| Puissance totale de raccordement: | 280,00 W |
| Appareil | |
| Type de batterie: | 1 x Lithium-Ion 3,7 V, 1,85 Wh |
| DMX channels: | 11/13/16 |
| DMX connection: | 5-pin and 3-pin XLR |
| Flash-rate: | 13 Hz |
| Color-wheel: | 9 dichroic plus white, CTO and CTB correction filters, UV filter |
| Rotating gobo wheel: | 8 gobos and open |
| Outside diameter of the gobos: | 14 mm |
| Image diameter of the gobos: | 7 mm |
| Maximum PAN-movement: | 630° |
| Maximum TILT-movement: | 270° |
| Beam angle: | 2° |
| Length of base (including handles): | 362 mm |
| Width of yoke: | 335 mm |
| Height (head horizontal): | 480 mm |
| Weight: | 15 kg |
| Spécifications juridiques | |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |