

FUTURELIGHT DSC-40 LED-Scan

PRO LED scanner with LUMINUS SST-90 LED

Réf. : 51839900

GTIN: 4026397447774



Caractéristiques:

- 12 or 14 DMX channels selectable for numerous applications
- Color-wheel with 7 different, dichroic color filters, UV filter and white
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Slot-in gobo system for exchanging gobos without tools
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- With gobo shake function
- Effect wheel with rotating 3-facet prism and 3D prism
- Macro function for rotating gobos/rotating prism combinations
- Frost filter
- Motorized focus
- Dimmer
- Strobe effect with 1-13 flashes per second via shutter
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Controlboard with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 7 built-in programs can be called up via DMX controller
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the control board or via an external controller and loaded into the memory
- Software-upload by optional accessory via DMX link
- Sound-controlled via built-in microphone

Logistique

EAN / GTIN: 4026397447774

Poids: 10,00 kg

Longueur: 0.68 m

Largeur: 0.38 m

Hauteur: 0.35 m

- DMX control via every standard DMX controller
- 1 LED
- Roue de gobo à gobos rotatifs
- Roue de gobo à gobos rotatifs, 7 gobos et ouvert
Gobos interchangeable
- Commandé via commande de la musique via microphone; RDM

Données techniques:

| | |
|-------------------------------------|---|
| Alimentation électrique: | 230 V AC, 50 Hz |
| Puissance totale de raccordement: | 115 W |
| Type de LED: | 1 |
| Mouvement de basculement max. TILT: | 45° positionnement |
| Mouvement de pivotement max. PAN: | 180° positionnement |
| Fréquence du flash: | 1 - 13 Hz |
| Équipement: | Roue de gobo à gobos rotatifs |
| Gobos: | Roue de gobo à gobos rotatifs, 7 gobos et ouvert Diamètre externe 27mm Diamètre de l'image 22mm Gobos interchangeables |
| Canaux DMX: | 12 |
| Commande: | Commande de la musique via microphone; RDM |
| Angle de départ (1/2 pic): | 12° |
| Couleur: | Noir |
| Dimension: | Largeur : 30 cm Profondeur : 57 cm Hauteur : 30 cm |
| Poids: | 7,90 kg |
| DMX channels: | 12/14 |
| DMX connection: | 3-pin XLR |
| Flash-rate: | 13 Hz |
| Sound-control: | via built-in microphone |
| LED type: | LUMINUS SST-90 |
| LED number: | 1 |
| Color-wheel: | 7 dichroic filters, UV filter and open |
| Rotating gobo-wheel: | 7 gobos and open |
| Outside diameter of the gobos: | 27 mm |
| Image diameter of the gobos: | 22 mm |
| Maximum PAN-movement: | 180° |
| Maximum TILT-movement: | 45° |
| Beam angle: | 12° |
| Dimensions (L x W x H): | 570 x 300 x 300 mm |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |

Contenu de la livraison:
