FUTURELIGHT EYE-36 RGB Moving-Head Wash

LED Moving Head washlight

Réf. : 51841328

GTIN: 4026397355277

L'article n'est plus disponible.

Description:

It's time for a revolution!
LEDs have revolutionized the illumination industry. In the meantime, they have reached almost every area and replace the well-tried illuminants or at least compete heavily with them. Moving heads have also got into the focus of diodes. The FUTURELIGHT EYE-36 MK2 sets an appropriate example. This head moving washlight is equipped with 36 LEDs (1 watt; 12 x red, 12 x blue, 12 x green), weighs less than its conventional competitors and thus is easy to transport. Beside the well-known and undeniable advantages of LEDs, such as the low power consumption and the low maintenance, the powerful EYE-36 offers a specialty. Because the radiation angle, normally 25°, can be changed via an optional, exchangeable lense module from 38° to 15°. Not only due to the different angles, the EYE-36 is a competitor which should be taken seriously.

Caractéristiques:

- Equipped with 36 x 1 W LEDs: 12 x red, 12 x blue, 12 x green
- Different radiation angles (from approx. 38° to approx. 15°) possible via optional, exchangeable lens module
- Stepless RGB color changing
- Masterdimmer
- Strobe effect
- Built-in sequences
- Compact housing
- Positioning within 540° PAN and 270° TILT
- Vector and tracking mode
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation

Logistique

EAN / GTIN: 4026397355277
Poids: 13,00 kg
Longueur: 0.41 m
Largeur: 0.42 m
Hauteur: 0.46 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

- Control board with 4-digit display for adjusting the DMX-starting address, PAN/TILT-Reverse, Program, Reset
- DMX control via every standard DMX controller

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	160 W
Mouvement de basculement max.TILT:	270° Positionnement
Mouvement de pivotement max. PAN:	540° Positionnement
Fréquence du flash:	1 - 18 Hz
Canaux DMX:	12
Angle de départ (1/2 pic):	38°
Dimension:	Longueur : 33,50 cm
Poids:	11,05 kg
DMX channels:	12
DMX connection:	3-pin XLR
Flash-rate:	18 Hz
LED number:	36
Beam angle:	38°
Length of base:	335 mm
Width of yoke:	305 mm
Height (head horizontal):	375 mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.