

FUTURELIGHT Stage Pixel Bar 10

Bar with narrow beam 10 x 15 W RGBW LED and frost plate

Réf. : 51841359

GTIN: 4026397561098



L'article n'est plus disponible.

Caractéristiques:

- Equipped with 10 high-power 4in1 LEDs in the colors red, green, blue and white
- Particularly bright illuminating power of the LEDs
- Collimator lenses for homogeneous beams with 4° beam angle
- Removable frost filter
- 4, 6, 8, 40 or 44 DMX channels selectable
- Each LED can be controlled individually
- Quick and easy control via Art-Net
- For use via appropriate lighting control software supporting Art-Net
- Programmable color change speed, strobe effect and dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with 1-18 flashes per second
- RGBW color mixing
- Static colors
- Internal programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Manual, sound, DMX- or ArtNet-controlled operation
- Sound-control via built-in microphone; adjustable sensitivity
- For large stage backgrounds in public places, main halls and lounges
- Hanging as well as standing installation possible
- Locking possibility at the mounting bracket
- Addressing via control panel with LCD screen and four operating buttons
- EtherCon input and output
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable with safety plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller

Logistique

EAN / GTIN: 4026397561098

Poids: 11,60 kg

Longueur: 0.97 m

Largeur: 0.24 m

Hauteur: 0.27 m

- 10 LED puissantes 15 W high-power 4in1 QCL RGBW (mélange de couleurs homogène)
- Effet stroboscope
- Commandé via ArtNet; stand-alone; DMX; Commande de la musique via Microphone; RDM
- Déjà préprogrammé pour %: Light´J; LED PC-Control 512; EASY SHOW 1
- Exempt de scintillements
- Avec un Angle de départ de 4°

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	170 W
Type de protection:	IP20
Branchement électrique:	Alimentation électrique via PowerCON (bleu), version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Sortie de courant:	1 x PowerCON (gris), version encastrable
Type de lampe:	Lampe LED
LED:	10 x 15 W high-power 4in1 QCL RGBW (mélange de couleurs homogène)
Fréquence du flash:	0 - 18 Hz
Canaux DMX:	4; 6; 8; 40; 44
Commande:	ArtNet; stand-alone; DMX; Commande de la musique via Microphone; RDM
Préprogrammé dans:	Light´J; LED PC-Control 512; EASY SHOW 1
Projection:	Exempt de scintillements
Angle de départ:	4°
Angle de départ (1/2 pic):	4°
Angle de départ (1/10 pic):	7°
Couleur du boîtier:	Noir
Dimension:	Longueur : 88 cm Profondeur : 15,9 cm Hauteur : 17,8 cm
Poids:	9,70 kg
Protocol:	Art-Net 3
Signal port:	2 x RJ45 (EtherCon)
DMX connection:	5-pin and 3-pin XLR
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle