

FUTURELIGHT DMH Quad-150 LED Moving Head

High performance LED Moving Head with 150 W COB LED in RGBW colors

Réf. : 51842100

GTIN: 4026397503142



L'article n'est plus disponible.

Caractéristiques:

- Equipped with a 150 W COB LED in RGBW colors
- 18, 20 or 23 DMX channels selectable
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism
- Macro function for rotating gobos/rotating prism combinations
- Stepless RGBW color changing
- Gobo wheel 1 with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Gobo wheel 2 with 7 static gobos plus open
- Exact positioning via 16 bit PAN/TILT movement resolution, gobo indexing, focus, iris
- Dimmer
- Motorized focus
- Frost filter
- Steplessly adjustable iris
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 630°, 540° - 90° offset or 540°
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Sound-controlled via built-in microphone
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc.

Logistique

EAN / GTIN: 4026397503142

Poids: 23,40 kg

Longueur: 0.69 m

Largeur: 0.48 m

Hauteur: 0.45 m

- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- DMX control via every standard DMX controller
- Commandé via Commande de la musique via Microphone; RDM
- Déjà préprogrammé pour %: Light Captain
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

| | |
|-------------------------------------|--|
| Alimentation électrique: | 100-240 V CA, 50/60 Hz |
| Puissance totale de raccordement: | 240 W |
| Mouvement de basculement max. TILT: | 265° Positionnement |
| Mouvement de pivotement max. PAN: | 630° Positionnement |
| Fréquence du flash: | 1 - 13 Hz |
| Gobos: | Diamètre externe 27mm Diamètre de l'image 22mm |
| Canaux DMX: | 18 |
| Commande: | Commande de la musique via Microphone; RDM |
| Préprogrammé dans: | Light Captain |
| Angle de départ (1/2 pic): | 17° |
| Couleur: | Noir |
| Dimension: | Largeur : 36,2 cm Profondeur : 39,3 cm Hauteur : 49,6 cm |
| Poids: | 20,05 kg |
| DMX channels: | 18/20/23 |
| DMX connection: | 5-pin and 3-pin XLR |
| Sound-control: | via built-in microphone |
| Wireless signal transmission: | 2.4 GHz (ISM) |
| Flash-rate: | 13 Hz |
| LED type: | Array Cluster 150 W, RGBW |
| LED number: | 1 |
| Beam angle: | 17° |
| Rotating gobo-wheel: | 7 gobos and open |
| Static gobo-wheel: | 7 gobos and open |
| Outside diameter of the gobos: | 27 mm |
| Image diameter of the gobos: | 22 mm |
| Maximum PAN-movement: | 630° |
| Maximum TILT-movement: | 265° |
| Dimensions (L x W x H): | 362 x 393 x 496 mm |
| Spécifications juridiques | |

Produit spécial: Non destiné à l'éclairage de la pièce dans les ménages

Utilisation: Éclairage pour effets de spectacle
