FUTURELIGHT PHF-1000 Moving-Head-Fogger

Innovative Moving Head fog machine

Réf. : 51843010

GTIN: 4026397267952

L'article n'est plus disponible.

Description:

Let's twist again!
Alright, it is probably not the wolf in sheep's clothing, but at least, it hides its true face at a first glance. Because this moving head is not a light emitting creature, but a fogger with the benefits of a such a device. This unit is not only able to produce a powerful smoke output, it also knows how to twist and turn. Moreover, the fogger has 8 built-in programs at its disposal, has no need for a special fluid and the number of scenes in Program Run can be modified at will. All that makes him a fast friend, especially for clubs or larger stages. Does not matter where the smoke is allowed to burgeon, it will definitely wow you!

Caractéristiques:

- Smoke machine with powerful smoke output
- Ideal for large discotheques or large stages
- Powerful output
- No need for special fluid
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 5 or 7 DMX channels selectable for numerous applications
- Timer-function in 7 channel mode
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- Positioning within 360° Pan and 265° Tilt
- Control board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset

Logistique

EAN / GTIN: 4026397267952
Poids: 18,00 kg
Longueur: 0.57 m
Largeur: 0.45 m
Hauteur: 0.46 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

- DMX control via every standard DMX controller
- Étendue de l'émission: Env. 5 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	110 W
Temps de chauffe:	Evn. 5 min
Étendue de l'émission:	Env. 5 m
Capacité du réservoir:	1 l
Canaux DMX:	5
Dimension:	Longueur : 58 cm
Poids:	15,20 kg
DMX channels:	5/7
DMX connection:	3-pin XLR
Maximum PAN-movement 360°:	in 2.0 s
Maximum TILT-movement 265°:	in 1.5 s
Smoke-output:	5 m
Warm-up time:	5 min.
Tank capacity:	approx. 1 l
Length of base:	580 mm
Width of yoke:	440 mm
Height (head horizontal):	500 mm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.