

## FUTURELIGHT LED PXB-160 Artnet Bar

LED bar for video and pixel mapping applications via Art-Net

Réf. : 51843130

GTIN: 4026397483406



**L'article n'est plus disponible.**

### Caractéristiques:

- Modular LED bar with 160 pixels for video and pixel mapping applications
- Quick and easy control via Art-Net
- Extra bright and colorful projection of videos, animations and graphics
- Modular concept allows the build-up of large areas
- Ideal for rental companies, stage/fair construction and fixed installation
- For use with MADRIX or any other lighting control software supporting Art-Net
- RGB SMD 5050 LEDs, covered by a smooth diffuser plate, provide excellent color rendering and wide viewing angles
- 2 x 16-digit LCD screen for menu settings
- Integrated web interface for comfortable configuration and firmware updates through a browser
- Useful software tool scans the network and identifies fixtures
- RDM-ready
- Signal processing via onboard receiver card
- Signal distribution via UTP cable
- Ethernet input and output
- Neutrik PowerCon input and output
- Movable mounting bracket for flexible installation
- Switch-mode power supply for operation between 100 and 240 volts

### Logistique

EAN / GTIN: 4026397483406

Poids: 5,75 kg

Longueur: 1.09 m

Largeur: 0.19 m

Hauteur: 0.23 m

### Données techniques:

Alimentation électrique: 100-240 V CA, 50/60 Hz

Puissance totale de raccordement: 60,00 W

Dimension: Longueur : 100 cm

|                           |                                                        |
|---------------------------|--------------------------------------------------------|
|                           | Profondeur : 10,9 cm<br>Hauteur : 14,5 cm              |
| Protocol:                 | Art-Net 3                                              |
| Pixel configuration:      | RGB SMD 5050                                           |
| Resolution:               | 160 pixels                                             |
| Pixel pitch:              | 25 mm                                                  |
| Brightness:               | 850 cd/m <sup>2</sup> (nits)                           |
| Viewing angle:            | 120°                                                   |
| Display refresh rate:     | 400 Hz                                                 |
| Video refresh rate:       | 60 fps                                                 |
| DMX channels:             | 480                                                    |
| Signal port:              | 2 x RJ45, CAT5e                                        |
| Dimensions (L x W x H):   | 1000 x 109 x 145 mm                                    |
| Weight:                   | 4.5 kg                                                 |
| Spécifications juridiques |                                                        |
| Produit spécial:          | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation:              | Éclairage pour effets de spectacle                     |