


EUROLITE LED IP Flood RGB 10mm 20°

LED RGB outdoor floodlight (IP65)

Réf. : 51914125

GTIN: 4026397294279



L'article n'est plus disponible.

Description:

In front of buildings or public places, the LED-PAR-64 and the LED floodlight are in real good hands. The colors are static and change automatically. Due to the LED technology, the LEDs shine amazingly bright. Moreover, these outdoor spots are able to strobe and thus have an attractive effect in addition to their nine integrated programs. To not be vulnerable to humidity, DIP switches were set aside. The spots can be linked and completely managed via a remote control.

Logistique

EAN / GTIN: 4026397294279

Poids: 4,60 kg

Longueur: 0,34 m

Largeur: 0,24 m

Hauteur: 0,28 m

Caractéristiques:

- Functions: static colors; automatic color change, 9 built-in programs and strobe effect with variable speed; Master/Slave
- Control in stand-alone mode and DMX programming via optional IR remote (necessary for use)
- DMX control via regular DMX controller (occupies 5 channels)
- Ideal LED luminary for outdoor use
- Locking possibility at the mounting bracket
- Perfect for public places and buildings
- 215 high-power 10mm LEDs
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Ready for connection with power cord and safety power plug
- Available in 20° or in 40° versions of the LED beam angle
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; DMX
- Déjà préprogrammé pour %: Light 'J
- Convient à une utilisation en extérieur IP65

- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	24 W
Type de protection:	IP65
Type de lampe:	Lampe LED
Canaux DMX:	5
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; DMX
Préprogrammé dans:	Light J
Angle de départ (1/2 pic):	20°
Couleur du boîtier:	Gris
Dimension:	Largeur : 30 cm Profondeur : 17,5 cm Hauteur : 21 cm
Poids:	4,10 kg
DMX channels:	5
DMX connection:	3-pin XLR
Protection grade:	IP65
LED number:	215
LED type:	10 mm
Beam angle:	20°
Dimensions (LxHxW):	300 x 210 x 175mm
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle