

EUROLITE LED IP PAR 36x1W RGB

Weather-proof DMX spotlight (IP65) with 36 x 1 W LED in red, green and blue

Réf. : 51914174

GTIN: 4026397434842



L'article n'est plus disponible.

Caractéristiques:

- Equipped with 36 x 1 W LED: 12 x red, 12 x green and 12 x blue
 - 3 or 5 DMX channels selectable for numerous applications
 - Beam angle approximately 15°
 - Locking possibility at the mounting bracket
 - Ideal as floor spot via additional bracket
 - Stepless RGB color change
 - 7 color presets and 4 built-in programs
 - DMX-controlled operation or stand-alone operation with Master/Slave function
 - Dimmer and strobe settings via DMX
 - Suitable for external use (IP65)
 - Perfect for architectural lighting in public places and buildings
 - Addressing via control panel with 4-digit LED display
 - Control via control panel with display or any regular DMX controller
 - Feed-through output allows to power another device
 - After every 8 spot the fixtures must have a renewed connection with the power mains
 - 36 LED puissantes 1 W high-power R/G/B (mélange de couleurs homogène)
 - Effet stroboscope
 - L'appareil est refroidi par refroidissement par convection passive
 - Commandé via stand-alone; DMX
 - Déjà préprogrammé pour %: Light´J; LED PC-Control 512
 - Avec un Angle de départ de 15°
- L'étendue des fournitures**
- 1 x câble adaptateur

Logistique

EAN / GTIN: 4026397434842

Poids: 4,30 kg

Longueur: 0.27 m

Largeur: 0.27 m

Hauteur: 0.32 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	50 W
Type de protection:	IP65
Branchement électrique:	Alimentation électrique via Connecteur fileté (M) IP 3 broches Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Sortie de courant:	1 x Connecteur fileté (F) IP 3 broches
Type de lampe:	Lampe LED
LED:	36 x 1 W high-power R/G/B (mélange de couleurs homogène)
Canaux DMX:	3; 5
Entrée DMX:	1 x Connecteur fileté (M) IP 3 broches
Sortie DMX:	1 x Connecteur fileté (F) IP 3 broches
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; DMX
Préprogrammé dans:	Light´J; LED PC-Control 512
Angle de départ:	15°
Angle de départ (1/2 pic):	15°
Couleur du boîtier:	Noir
Dimension:	Largeur : 24 cm Profondeur : 20 cm Hauteur : 32 cm
Poids:	3,85 kg
Spécifications juridiques	
Produit spécial:	Non destiné à l'éclairage de la pièce dans les ménages
Utilisation:	Éclairage pour effets de spectacle