

EUROLITE Safety bond AG-35FA 6x1000mm up to 35kg

Câble de sécurité approuvé

Réf. : 58010368

GTIN: 4026397496871



L'article n'est plus disponible.

Description:

EUROLITE Safety bonds

The EUROLITE safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The safety bonds are manufactured by a renowned German supplier and are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can secure loads above persons with these safety bonds in all areas where the BGV C1 is required.

Caractéristiques:

- Suitable for securing loads above persons
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- 6 mm quick link (form A) included
- Test report according to DIN EN 10204 as download
- Correspond DIN EN 12385-4:2008-06 et DIN 56927:2009-03
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Logistique

EAN / GTIN: 4026397496871

Poids: 0,23 kg

Longueur: 0.17 m

Largeur: 0.18 m

Hauteur: 0.03 m

Données techniques:

Charge à protéger (BGV C1):	Max. 35 kg
Construction à base de câbles:	6 x 19 FC
Classe de résistance du câble:	1770
Norme:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Résistance à la rupture du câble:	1770 N/mm ²
Surface des fils:	Galvanisé
Plage de température:	-40° C - +100° C
Dimension:	Longueur : 1 m
Poids de longueur:	0,125 kg/m
Temperature range:	-40° C to +100° C
Rope length:	1.00 m
Rope diameter:	6.00 mm
Rope type:	Round strand rope
Nominal tensile strength:	1770 N/mm ²
Strength classification:	1770