

## EUROLITE Câble de fixation 1500 x 10 mm

Câble de fixation, câble de sécurité

Réf. : 58010491

GTIN: 4026397192919



### Description:

EUROLITE Lifting ropes, safety bonds

The EUROLITE lifting ropes, safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The lifting ropes, safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The lifting ropes, safety bonds are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can install and secure loads above persons with these lifting ropes, safety bonds in all areas where the BGV C1 is required.

Use as attachment gear

These ropes are stamped with a WLL describing the maximum load when used for general lifting purposes. For all areas where the BGV C1 is required, the correct lifting rope must be selected only by calculating with safety-factor 12. According to this calculation, the maximum load of this rope is 450 kg (single-stranded).

### Caractéristiques:

- Câble à torons ronds 6 x 19 avec insert en fibre
- Avec deux cosses
- Pour fixer et sécuriser des charges au-dessus des personnes
- Correspond DIN EN 12385-4:2008-06 et DIN 56927:2009-03
- Corde à cosse et raccord
- Examiné par le LGA
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

### Logistique

EAN / GTIN: 4026397192919

Poids: 1,48 kg

Longueur: 0.31 m

Largeur: 0.23 m

Hauteur: 0.06 m

**Données techniques:**

|                                   |                                           |
|-----------------------------------|-------------------------------------------|
| Charge maximale WLL (5 fois):     | 1050 kg                                   |
| Construction à base de câbles:    | 6 x 19 FC                                 |
| Classe de résistance du câble:    | 1770                                      |
| Norme:                            | DIN EN 12385-4:2008-06, DIN 56927:2009-03 |
| Résistance à la rupture du câble: | 1770 N/mm²                                |
| Surface des fils:                 | Galvanisé                                 |
| Couleur:                          | Argenté                                   |
| Plage de température:             | -40° C - +100° C                          |
| Dimension:                        | Longueur : 150 cm<br>Diamètre : Ø 1 cm    |
| Poids:                            | 1,47 kg                                   |
| Poids de longueur:                | 0,359 kg/m                                |

**Contenu de la livraison:**