


EUROLITE Câble en acier 1000 x 4 mm noir à cosse

Câble de fixation, câble de sécurité

Réf. : 5801049C

GTIN: 4026397376111



Description:

EUROLITE Lifting ropes, safety bonds

The EUROLITE lifting ropes, safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The lifting ropes, safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The lifting ropes, safety bonds are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can install and secure loads above persons with these lifting ropes, safety bonds in all areas where the BGV C1 is required.

Use as attachment gear

These ropes are stamped with a WLL describing the maximum load when used for general lifting purposes. For all areas where the BGV C1 is required, the correct lifting rope must be selected only by table 2 of BGI 810-3:2007-03. According to this table, the maximum load of this rope is 70 kg (single-stranded).

Use as safety bond

The correct safety bond must be selected only by table 9 of BGI 810-3:2007-03. According to this table, the maximum load of this safety bond is 15 kg.

Logistique

EAN / GTIN: 4026397376111

Poids: 0,08 kg

Longueur: 0.10 m

Largeur: 0.08 m

Hauteur: 0.03 m

Caractéristiques:

- Câble à torons ronds 6 x 19 avec insert en fibre
- Avec deux cosses
- Pour fixer et sécuriser des charges au-dessus des personnes
- Correspond DIN EN 12385-4:2008-06 et DIN 56927:2009-03
- Corde à cosse

- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Charge maximale WLL (5 fois):	175 kg
Construction à base de câbles:	6 x 19 FC
Classe de résistance du câble:	1960
Norme:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Résistance à la rupture du câble:	1770 N/mm²
Surface des fils:	Galvanisé
Couleur:	Noir
Plage de température:	-40° C - +100° C
Dimension:	Longueur : 100 cm Diamètre : Ø 0,40 cm
Poids:	0,08 kg
Poids de longueur:	0,0554 kg/m

Contenu de la livraison: