

ALUTRUSS Traverse 1 point DECOLOCK DQ1-1000

Système de traverse 1 point universel de conception légère

Réf. : 60301482

GTIN: 4026397497496



Prix de catalogue: 44.63 €

TVA 19% incl.

Description:

DECOLOCK DQ1 1-point truss system
DECOLOCK DQ1 is a 1-point truss system made of aluminum. The individual elements are connected via a cone, pivot and pin.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

With DECOLOCK, you can realize compact installations with low self weight, e. g. for shop displays, shop decorations, exhibitions, interior design, fair booths, discotheques and theatres.

With DECOLOCK DQ1, decorative frames with advertising signs, transmission canvas etc. can be realized.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

Caractéristiques:

- Alliage d'aluminium pour un look classique et high-tech
- DQ1 est particulièrement adapté comme structure de cadre pour les films de projection
- Montage rapide, efficace et fiable grâce aux connecteurs coniques Quick-Lock
- Un vaste choix de longueurs, d'éléments circulaires et d'angles offre un maximum de flexibilité
- Constructions spéciales selon les spécifications du client sur demande
- Tube porteur: 35 mm

Logistique

EAN / GTIN: 4026397497496

Poids: 0,70 kg

Longueur: 1.00 m

Largeur: 0.04 m

Hauteur: 0.04 m

- Chaque couleur RAL disponible sur demande
- Modèles à disponibles
- Made in Europe
- Pour des domaines d'application tels que: Agencement de magasin; Théâtre; Agencement de salons et magasin; Installation; Scène
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

L'étendue des fournitures

- 1 x set de connecteurs

Données techniques:

Tube porteur:	35 mm x 2 mm; 35 mm
Procédé de soudure:	Impulsion WIG
Matière de soudure:	AlMg 5
Matériau du tube:	AlMgSi 0,5
Couleur:	Couleurs alu; chaque couleur RAL disponible sur demande
Dimension:	Longueur : 1 m Largeur : 3,50 cm Hauteur : 3,50 cm
Poids:	690 g