

## ALUTRUSS Élément en T 3 voies 90° noir DQ3-SPAT38 DECOLOCK

Système de traverse 3 points universel de conception légère

Réf. : 60302038

GTIN: 4026397667097



**Prix de catalogue: 351.05 €**

TVA 19% incl.

### Description:

DECOLOCK DQ3 3-point truss system  
DECOLOCK DQ3 is a 3-point truss system made of aluminum. The individual elements are connected via three cones, pivots and pins.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The three main chords are made of 35 mm aluminum tube with 2 mm wall thickness and offer sufficient strength at a low weight. The braces have a diameter of 10 mm with 2 mm wall thickness and provide the system with a decorative appearance.

With DECOLOCK, you can realize compact installations with low self weight, e. g. for shop displays, shop decorations, exhibitions, interior design, fair booths, discotheques and theatres.

DECOLOCK is primarily designed for decorative installations and can be used for permanent or temporary installations due to its highly aesthetic appearance. The advantages of this system are the compact construction with 220 and 195 mm outer dimensions, low weight, optimum strength along with easy and quick assembly.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

### Logistique

EAN / GTIN: 4026397667097

Poids: 3,10 kg

Longueur: 0.67 m

Largeur: 0.44 m

Hauteur: 0.32 m

## Caractéristiques:

---

- Poids réduit
- Montage facile
- Tube porteur: 35 mm
- Pour des domaines d'application tels que: Agencement de magasin; Agencement de salons et magasin

### L'étendue des fournitures

- 2 x set de connecteurs

## Données techniques:

---

|                                  |   |
|----------------------------------|---|
| Construction:                    | Montage facile  |
| Tube porteur:                    | 35 mm x 2 mm; 35 mm                                       |
| Procédé de soudure:              | Impulsion WIG   |
| Matière de soudure:              | AlMg 5  |
| Couleur:                         | Noir, thermolaqué   |
| Entretoise diamètre x épaisseur: | 10 x 2 mm   |
| Dimension:                       | Longueur : 60,50 cm<br>Largeur : 40 cm<br>Hauteur : 22 cm |
| Poids:                           | 2,85 kg   |