

EUROLITE DMX Stage Control 136 controller

Versatile DMX controller

Réf. : 70064535

GTIN: 4026397220353



L'article n'est plus disponible.

Description:

Let's bring them together! On this DMX Stage control, parcans and movinglights can be operated simultaneously. It fits best in little clubs, hotel dicotheques or on manageable live events, where only a few programs are needed. The controller is easy to use and is seperated in 128 movinglight- and 8 parcan-channels.

Caractéristiques:

- 136 control channels DMX out and MIDI in
- 8 channel-faders with LED
- Fade Time fader with LED for adjusting the step time
- Master-fader with LED for adjusting the total output level
- Speed-fader for adjusting the program-speed
- Audio-fader with LED for adjusting the music sensitivity
- CF memory card for programs
- LCD display
- External power supply
- 6.3 mm jack connection for footswitch (scene steps)
- 0/10 V-output via one 5-pin DIN-socket for fog machine
- Simultaneous and independent control of scanner and parcan section
- Dimmer: Manual control of the channels via sliders
- Full On: all channels can be switched on together
- Blackout-function
- Program speed adjustable via speed-fader or Tap Sync-button
- Sound-control via external signal or integrated microphone
- Sound to light via RCA socket
- Rack mounting plates included

Logistique

EAN / GTIN: 4026397220353

Poids: 3,75 kg

Longueur: 0.58 m

Largeur: 0.32 m

Hauteur: 0.16 m

- Rack installation with 4 units
- Scanner Section:
 - 128 control channels for 8 scanners with up to 16 DMX channels
 - 12 pages with up to 8 scenes can be programmed
 - 8 chasers each with up to 99 steps
 - Programmable speed and fade time
 - Patch possibility
 - Joystick with fine mode and 4 step buttons
- Dimmer Section:
 - 8 dim fader channels and 1 master fader
 - 12 pages with up to 6 scenes can be programmed
 - 6 chasers each with 99 steps
 - Speed, tap-sync und audio fader
 - Step function
 - Standby and full-on
 - Peut envoyer jusqu'à 136 canaux DMX
 - Commandé via DMX
 - Boîtier du pupitre

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	6,00 W
Type de protection:	IP20
Canaux DMX:	Sortie 136
Commande:	DMX
Couleur:	Noir
Conception du boîtier:	Boîtier du pupitre
Dimension:	Largeur : 21,5 cm Profondeur : 6,4 cm Hauteur : 28 cm
Poids:	3,30 kg
	via 12 V DC, 600 mA power unit included in the delivery
Number of control channels:	136
Sound-control:	via built-in microphone or via audio-input
Audio-input:	Jack
Audio-sensitivity:	0.1-1 V
DMX512 output:	3-pin XLR connector with polarity selector
Free chasers:	8 for scanner section and 6 for dimmer section
Dimensions (L x W x H):	483 x 180 x 93 mm
	Rack installation with 4 u
Minimum mounting depth:	100 mm