

## EUROLITE PSS-4/150 Pixel String

Flexible LED pixel string

Réf. : 80503361

GTIN: 4026397423495



**L'article n'est plus disponible.**

### Caractéristiques:

- Flexible pixel string with ultra-bright TCL LEDs
- 32 pixels with 4 LEDs each
- Bright and colorful projection of videos and graphics
- Can be arranged into virtually any form even on uncommon surfaces for creative freedom
- Modular concept allows build-up of large video displays for clubs, stages, shops and various other environments - also for billboards on buildings
- Can be extended up to 40 meters with 340 pixels
- IP65 for indoor and outdoor use
- Pixels individually controllable
- Independent control of color, effects and animations
- Control per network protocol with PC software or PSS media player (accessories)
- Control also possible per MADRIX, DMX and Artnet
- Large operating range from -20° to +50° C

### Logistique

EAN / GTIN: 4026397423495

Poids: 0,46 kg

Longueur: 0.30 m

Largeur: 0.20 m

Hauteur: 0.08 m

### Données techniques:

Puissance totale de raccordement: 260,00 W

Type de protection: IP65

Dimension: Largeur : 2,3 cm  
Profondeur : 1 cm  
Hauteur : 3,8 cm

Poids: 400 g

|                           |  |
|---------------------------|--|
| Pixel pitch:              | 150 mm   |
| Pixel configuration:      | 4 RGB LEDs (TCL)                                       |
| Pixels per string:        | 32   |
| Pixel size (W x D x H):   | 23 x 38 x 10 mm  |
| String length:            | 5 m  |
| Max. string length:       | 40 m   |
| Total max. pixels:        | 340  |
| Brightness:               | 2.5 cd per pixel                                       |
| Bit depth per color:      | 16   |
| Bit depth per pixel:      | 48   |
| Viewing angle:            | 120° x 120°  |
| Lifetime:                 | approx. 80000 hours                                    |
| Control protocol:         | TCP/IP   |
| Control system:           | PSS-4  |
| Display mode:             | synchronous to video source                            |
| Protection grade:         | IP65   |
| Material:                 | clear polycarbonate                                    |
|                           | black cable  |
| Operating temperature:    | -20 to 50 °C   |
| Power supply:             | 15 V DC via control system PSS-4                       |
| Spécifications juridiques |  |
| Produit spécial:          | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation:              | Éclairage pour effets de spectacle                     |