

OMNITRONIC GCS-510 Ceiling Speaker 10W/pa

HiFi ceiling mount speaker with firedome

Réf. : 80710114

GTIN: 4026397349139



L'article n'est plus disponible.

Caractéristiques:

- 2-way system with 13 cm woofer (5") and 1.5" tweeter
- For 8-ohm and 100 V systems
- Front-mounted 4-step power selector
- Steel firedome for safety in case of fire
- Sturdy steel grille in off-white
- Installation via drill holes in the housing
- Incl. mounting bracket for secure installation

Logistique

EAN / GTIN: 4026397349139

Poids: 8,35 kg

Longueur: 0.77 m

Largeur: 0.38 m

Hauteur: 0.20 m

Données techniques:

Capacité de charge:	Programme: 20W Nominale: 10W RMS (PA 100 V) Nominale: 10W RMS (8 Ohm)
Plage de fréquence:	75 - 18000 Hz
Sensibilité:	86 dB
Pression acoustique max.:	102 dB
Impédance:	8 Ohm; technologie PA 100 V
Prise de puissance:	1,25W; 2,5W; 5W; 10W RMS via extrémités ouvertes du câble sélectionnable
Enceinte:	1 x Boumeur 5" 1 x tweeter 1,5"

Type d'enceinte:	Enceinte encastrable
Dimension:	Largeur : 36 cm Profondeur : 34,5 cm Hauteur : 15 cm
Poids:	7,25 kg