

OMNITRONIC EM-550B Entertainment Mixer

Mixer multifunzione per installazione a 5+2 canali, nero

Art.n.: 10007101

GTIN: 4026397466423



L'articolo non è più disponibile.

Features :

- 5 input channels with recessed gain controls on the rear panel, signal LED and super smooth dual-rail channel faders
- 2 separate microphone channels with level control, 3-way equalizer and talkover button
- Talkover level and response time adjustable
- Pre-fader listening (CUE) to the stereo input channels via adjustable headphone output
- Color illuminated rotary controls and rubber buttons
- 1 additional line input with level control on the front panel
- 2 adjustable master outputs with 3-way equalizer and 10-digit stereo LED level meter
- 1 adjustable booth output with mono/stereo selector switch
- 2 record outputs (independent of the master channels) with on/off switch for microphone signals
- Inputs: 9 x line (stereo RCA), 2 x line/phono (stereo RCA), switchable; 2 x microphone (XLR/6.3 mm jack) and headphones (6.3 mm jack)
- Outputs: 2 x master (optionally 3-pin XLR or stereo RCA), 1 x booth (stereo RCA) and 2 x record (stereo RCA)
- Operation via supplied power unit
- Rack installation, 2 U
- Ideal for restaurants, bars, theme parks, hotels and all applications where microphones need to be mixed with music (e.g. karaoke)
- Montaggio su rack (19") 48,3 cm 2 U

Logistica

EAN / GTIN: 4026397466423

Peso : 4,25 kg

Lunghezza : 0.61 m

Larghezza : 0.16 m

Altezza : 0.14 m

Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza totale installata: 35,00 W

Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite connettore a vite a 3 poli (M) versione da incasso cavo di alimentazione con spina europea (in dotazione)
Intervallo di frequenza:	20 - 20000 Hz
Rapporto segnale-rumore:	>65 dB
Equalizzatore:	Master: 2 x regolatore a 3 bande Stereo
Struttura della custodia:	Montaggio su rack (19") 48,3 cm 2 U
Misure:	Larghezza: 48,3 cm Profondità: 11,5 cm Altezza: 8,9 cm
Peso:	3,80 kg
Inputs:	
Microphone 1.2	combined XLR/6.3 mm jack (1/4") (bal.)
Minimum input voltage:	1 mV RMS
Line 1-8, Aux 1.2:	stereo RCA
Minimum input voltage:	150 mV RMS
Phono 1.2:	stereo RCA
Minimum input voltage:	3 mV RMS
Outputs:	
Master 1.2:	stereo RCA, stereo XLR
Output voltage:	0.75 V/1.5 V RMS (switchable)
Booth:	stereo RCA (switchable to mono operation)
Output voltage:	0.75 V RMS
Record:	stereo RCA
Output voltage:	0.75 V RMS
Headphones output:	6.3 mm stereo jack (min. 8 ohms)
Tone control (microphone 1.2; output 1.2):	
4 x High:	-12 dB to +12 dB/ 10 kHz
4 x Mid:	-12 dB to +12 dB/ 1 kHz
4 x Low:	-12 dB to +12 dB/ 100 Hz
Talkover attenuation:	-15 dB
Distortion:	0.03 %
Dimensions (WxHxD):	483 x 115 x 90 mm (19", 2 U)