

OMNITRONIC EM-650 Entertainment Mixer

Multifunctional 5+2-channel mixer with 3 zones, silver

Art.n.: 10007110

GTIN: 4026397355826



L'articolo non è più disponibile.

Descrizione :

OMNITRONIC Entertainment Mixer Series

The modern entertainment industry, especially hotels, bars or theme parks, requires very high standards in quality and features for sound devices.

The OMNITRONIC EM-series is especially designed for this industry and offers the highest flexibility and quality in very small mixer casings.

The EM-series offers a variety of connection possibilities and also convinces by an ergonomic design and easy use.

The special housing design and the state-of-the-art construction are further reasons which make the EM-series the first choice for installers.

Features :

- 3 zones with routing facility of all input channels as desired
- 5 input channels with recessed gain controls on the rear panel, signal LED and super smooth dual-rail channel faders
- 2 microphone channels with level control, LED level meter, 3-way equalizer and talkover button
- Talkover level and response time adjustable
- Pre-fader listening (CUE) to the stereo input channels via adjustable headphone output
- Color illuminated rotary controls and rubber buttons
- Zone outputs with level control, 3-way equalizer and 10-digit stereo LED level meter
- 2 record outputs (independent of the master channels) with routing facility of all zone outputs as desired
- Inputs: 8 x line (stereo RCA), 2 x line/phono (stereo RCA), switchable; 2 x microphone (XLR/6.3 mm jack) and headphones (6.3 mm jack)
- Outputs: 3 x master (optionally 3-pin XLR or stereo RCA) and 2 x record (stereo RCA)
- Operation via supplied power unit

Logistica

EAN / GTIN: 4026397355826

Peso : 4,35 kg

Lunghezza : 0.61 m

Larghezza : 0.15 m

Altezza : 0.14 m

- Rack installation, 2 U
- Ideal for restaurants, bars, theme parks, hotels and all applications where microphones need to be mixed with music (e.g. karaoke)
- Montaggio su rack (19") 48,3 cm 2 U

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz 15V
Potenza totale installata:	35,00 W
Classe di protezione:	CL III
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite connettore a vite a 3 poli (M) versione da incasso cavo di alimentazione con spina europea (in dotazione)
Intervallo di frequenza:	20 - 20000 Hz
Rapporto segnale-rumore:	>65 dB
Distorsione armonica totale:	<0,03 % a 1 kHz
Colore della custodia:	Argento
Controlli:	Interruttore di rete, Talkover regolabile, Interruttore sorgente
LED di stato:	Segnale, Indicatore del livello del canale, Indicatore del livello master, Peak, Sorgente del canale; CUE, talkover, ON AIR, routing
Collegamenti:	Ingresso: line/phono via 2 x RCA stereo Ingresso: line via 8 x RCA stereo Ingresso: microfono via 2 x presa combinata XLR a 3 poli/jack da 6,35 mm (F) versione da incasso Uscita: Master via 6 x XLR a 3 poli Uscita: Master via 3 x RCA stereo Uscita: rec. via 2 x RCA stereo Uscita: Cuffie via 1 x Presa jack (stereo) da 6,3 mm versione da incasso
Canali:	Canale di ingresso: 2 x Stereo with Interruttore line/phono via RCA, channel control via Fader, regolatore a 3 bande EQ 100Hz/1kHz/10kHz, Regolatore del guadagno, interruttore master di routing bus, Interruttore CUE Canale di ingresso: 3 x Stereo with Interruttore line-line via RCA, channel control via Fader, regolatore a 3 bande EQ 100Hz/1kHz/10kHz, Regolatore del guadagno, interruttore master di routing bus, Interruttore CUE Canale del microfono: 2 x Mono via Presa combinata (XLR/JACK), channel control via manopola, interruttore master di routing bus, Interruttore ON AIR Uscita master: 3 x Stereo via XLR o RCA, channel control via manopola, Interruttore sorgente Rec. Uscita: 1 x Stereo via RCA, channel control via manopola, funzione cue mix Uscita per auricolari: 1 x Stereo via jack, channel control via manopola
Struttura della custodia:	Montaggio su rack (19") 48,3 cm 2 U
Misure:	Larghezza: 48,3 cm

Profondità: 11,7 cm

Altezza: 8,9 cm

Peso:

4 kg
