

OMNITRONIC LH-071 Active Dual DI Box

Dual DI box/splitter

Art.n.: 10355071

GTIN: 4026397401363



L'articolo non è più disponibile.

Features :

- Active 2-channel DI box with split mode
- 2 high-impedance signal inputs via combo connectors (XLR/6.3 mm jack)
- 2 low-impedance XLR outputs
- Converts 2 separate unbalanced line inputs (e.g. instruments) into 2 balanced XLR outputs, for connecting a mixer
- Switchable to split mode (input 1 routes the signal to both outputs)
- Input sensitivity switchable: +20 dB, 0 dB, -30 dB
- Ground-lift switch eliminates signal interference and ground loop problems
- Phase can be switched
- Hi-cut 10 kHz switchable
- Modern convex housing design with rubber corners for safe positioning
- Stackable
- Cables can be routed under the housing
- Operation with 9 V battery (included)
- Funzionamento a pila/batteria ricaricabile possibile

Logistica

EAN / GTIN: 4026397401363

Peso : 0,83 kg

Lunghezza : 0.23 m

Larghezza : 0.15 m

Altezza : 0.09 m

Dati tecnici :

Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite connettore cavo (M) versione da incasso cavo di alimentazione con alimentatore a spina (in dotazione)
Pila:	1 x Blocco E 9,0 V 6F22 zinco-carbone presente
Intervallo di frequenza:	10 - 30000 Hz

Misure:	Larghezza: 15 cm Profondità: 6 cm Altezza: 13 cm
Peso:	0,64 kg
Current consumption:	approx. 65 mA
Input impedance:	470 kohms
Output impedance:	600 ohms
Maximum output level:	6 dBu
Dynamic range:	>100 dB
Hi cut:	10 kHz
Input connectors:	2 x combo XLR/6.3 mm jack
Output connectors:	2 x XLR, bal.
THD:	0.5 %