

## OMNITRONIC XO-23S Active crossover

High-quality stereo crossover

Art.n.: 10355630

GTIN: 4026397393101



L'articolo non è più disponibile.

### Features :

- 2-way stereo operation / 3-way mono operation
- Additional Subwoofer output
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency Low/High band 100 Hz to 7 kHz
- Frequency range of crossover frequency Subwoofer 50 Hz to 350 Hz
- Individual output level controls for all bands
- Low cut switch
- Phase invert control
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

### Logistica

EAN / GTIN: 4026397393101

Peso : 2,50 kg

Lunghezza : 0.54 m

Larghezza : 0.20 m

Altezza : 0.07 m

### Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza totale installata: 10,00 W

Misure: Larghezza: 48,3 cm  
Profondità: 14,7 cm  
Altezza: 4,45 cm

Peso: 2,15 kg

Slope: 24 dB / octave

|                         |                           |
|-------------------------|---------------------------|
| Operation modes:        | 2-way stereo/mono         |
| Input:                  | Mono/stereo               |
| Input impedance:        | 10/20 kohms (unb./bal.)   |
| Output:                 | Mono/stereo               |
| Output impedance:       | 300/150 kohms (unb./bal.) |
| In/out connectors:      | XLR                       |
| S/N ratio:              | >100 dB                   |
| THD:                    | 0.05%                     |
| Input gain:             | -- to +6 dB               |
| Ouptut gain:            | -- to +12 dB              |
| Low cut:                | 30 Hz, -3 dB              |
| Phase adjustment:       | 0-180°                    |
| Dimensions (W x D x H): | 483 x 147 x 46 mm         |