

OMNITRONIC XO-23SB Active crossover

Deviatore di frequenza attivo, stereo a 2 vie e funzionamento mono a 3 vie

Art.n.: 10355631

GTIN: 4026397382907



L'articolo non è più disponibile.

Features :

- 2-way stereo operation
- Additional Subwoofer output switchable from mono to stereo
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency Low/High band 100 Hz to 7 kHz
- Frequency range of crossover frequency Subwoofer 50 Hz to 350 Hz
- Individual output level controls for all bands
- Low cut switch
- Phase invert control
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Logistica

EAN / GTIN: 4026397382907

Peso : 2,50 kg

Lunghezza : 0.56 m

Larghezza : 0.20 m

Altezza : 0.07 m

Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza totale installata: 10,00 W

Misure: Larghezza: 48,3 cm
Profondità: 14,7 cm
Altezza: 4,45 cm

Peso: 2,10 kg

Slope: 24 dB / octave

Operation modes:	2-way stereo/mono
Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/out connectors:	XLR
S/N ratio:	>100 dB
THD:	0.05%
Input gain:	-- to +6 dB
Ouptut gain:	-- to +12 dB
Low cut:	30 Hz, -3 dB
Phase adjustment:	0-180°
Dimensions (W x D x H):	483 x 147 x 46 mm