

PSSO®

QCA-10000 4-Channel SMPS Amplifier

Amplificatore PA stereo in class I con alimentatore switching, 4 x 2500 W RMS (2 Ohm), 4 x 2100 W RMS (4 Ohm)

Art.n.: 10451697
GTIN: 4026397513370



PSSO®

QCA-10000 4-Channel SMPS Amplifier

Amplificatore PA stereo in class I con alimentatore switching, 4 x 2500 W RMS (2 Ohm), 4 x 2100 W RMS (4 Ohm)

Art.n.: 10451697
GTIN: 4026397513370

Features :

- 4-channel PA amplifier with class I circuitry
- 4 x 2100 W/4 ohms
- Low weight and height due to integrated switch mode power supply
- Reliable power amp with high impulse stability for a wide range of applications (e.g. compact PAs, multi-way PAs, concerts)
- 3 operating modes can be selected (stereo, parallel or bridged)
- 4 level controls for precise level adjustment
- Input sensitivity adjustable
- LED VU meter and LEDs for activated protective circuit (protect), overload (clip), and signal per channel
- Speaker switch-on delay
- Complete protection set against short-circuit, overheat, clipping, overload, DC voltage and VHF signals
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs