

OMNITRONIC HDA-2.2 Amplifier

3-channel amplifier 2 x 160 W + 350 W @ 4 ohms

Art.n.: 10452350

GTIN: 4026397245493



L'articolo non è più disponibile.

Descrizione :

With up to 2,300 watts of built-in power, the HDA series is the perfect power source for various professional PA systems capable of high volume. Thanks to its three-channel design and the integrated frequency filters the series is optimized for stereo operation with satellite cabinets and a mono subwoofer. This series is ideally suited for bars and clubs, restaurants, dancing schools and gyms.

Features :

- 2 x 100 W + 200 W @ 8 ohms
- 2 x 160 W + 350 W @ 4 ohms
- Low Cut switch on the rear panel
- Rotary control for adjusting the upper crossover frequency (Hi Cut) of the subwoofer
- 3 gain controls
- All operation modes controllable via LEDs, can be switched off
- Signal inputs via XLR female or terminal block
- Speaker connection via terminal block or speaker jacks
- Many protection circuits for optimized equipment protection
- Forced fan cooling
- Very rugged housing
- Rack installation

Logistica

EAN / GTIN: 4026397245493

Peso : 21,50 kg

Lunghezza : 0.55 m

Larghezza : 0.54 m

Altezza : 0.14 m

Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza in uscita:	Massimo 670 W
Intervallo di frequenza:	20 - 20000 Hz
Misure:	Larghezza: 48,3 cm Profondità: 45 cm Altezza: 8,9 cm
Peso:	20 kg
Power output sine:	
Stereo 4 ohms	2 x 160 W + 350 W
Stereo 8 ohms	2 x 100 W + 200 W
Damping factor:	>250
Distortion factor:	0.05 %
Signal-to-Noise ratio:	>95 dB
Min. input sensitivity:	0.775 V RMS
Input impedance:	10 kohms (unbalanced), 20 kohms (balanced)
Output impedance:	>0.02 ohms
Slew rate:	20 V/ μ sec
LED indicators (per channel):	Clip, Protect, Signal
Minimum mounting depth:	470 mm