

## OMNITRONIC C-60A active white 2x

Active 2-way speaker pair with mount, 6,5" woofers and 60 W RMS

Art.n.: 11036721

GTIN: 4026397356373



**L'articolo non è più disponibile.**

### Features :

- Dedicated PA speaker system for fixed installations
- 2-way bass-reflex system for powerful bass
- 16.5 cm woofer (6.5") and 2.5 cm dome tweeter (1")
- 2-way tone control and level control
- Signal input and output via balanced XLR connectors
- White or titanium plastic housing (ABS) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket for ceiling or wall installation
- Ideal for PA applications in restaurants, bars, discos, shops, conferences, etc.

### Logistica

EAN / GTIN: 4026397356373

Peso : 9,70 kg

Lunghezza : 0.43 m

Larghezza : 0.24 m

Altezza : 0.34 m

### Dati tecnici :

|                          |                                             |
|--------------------------|---------------------------------------------|
| Alimentazione elettrica: | 230 V AC, 50 Hz                             |
| Capacità di carico:      | Programma: 100W<br>Nominale: 60W RMS        |
| Intervallo di frequenza: | 50 - 20000 Hz                               |
| Sensibilità:             | 89 dB (1W/1m)                               |
| Collegamenti:            | Ingresso: Altoparlante via 2 x XLR a 3 poli |
| Altoparlante:            | 1 x 6,5" Woofer                             |
| Colore:                  | Bianco                                      |
| Misure:                  | Larghezza: 20,5 cm                          |

|                         |                                            |
|-------------------------|--------------------------------------------|
|                         | Profondità: 18 cm<br>Altezza: 28,5 cm      |
| Peso:                   | 9,10 kg                                    |
| Components:             | 16.5 cm woofer (6.5"), 2.5 cm tweeter (1") |
| Input:                  | 3-pin XLR                                  |
| Output:                 | 3-pin XLR                                  |
| Sensitivity:            | 89 dB                                      |
| Dimensions (H x W x D): | 285 x 205 x 180 mm                         |