

OMNITRONIC AS-1500 MKII Active system

Powerful compact active PA system, 1500 watts

Art.n.: 11038822

GTIN: 4026397404456



Features :

- Mobile subwoofer/satellite system with integrated 3-channel amplifier, 2-way crossover and limiter
- Very high durability and high SPL - ideal for solo entertainers, bands and mobile DJs
- Several AS-1500 systems can be used to set up large PA systems
- Integrated SMPS
- 45 cm subwoofer in bass-reflex cabinet provides powerful, dry bass
- Tops with 25 cm bass-midrange speakers and 2 cm constant directivity horn with coil-driver and passive 2-way crossover
- Balanced inputs via combo jacks (XLR/6.3 mm) and parallel outputs (XLR) for feed-through of the input signal to a second system
- Satellite speaker connection via lockable Speaker plugs
- Complete protection set, among others with opto limiter and subsonic filter against extremely low frequencies
- Level controls for the subwoofer and the satellite speakers, as well as bass and treble EQ for the the satellite speakers
- Subwoofer in multiplex wood cabinet, satellite speakers in MDF cabinet with scratch-resistant lacquer surface and impact-resistant steel grille with acoustic foam
- Satellite speakers with stand flanges and trapezoidal shape for easy clustering
- Subwoofer also with D20 thread for accepting a speaker stand tube and two swivel castors and two fixed castors for easy transportation
- Tops can be used lying, standing, suspended, mounted to a stand or to a stand tube on the subwoofer
- Subwoofer can be used lying or standing
- Delivery includes two 5-meter speaker cables from the subwoofer to the satellite speakers

Logistica

EAN / GTIN: 4026397404456

Peso : 30,35 kg

Lunghezza : 0.68 m

Larghezza : 0.35 m

Altezza : 0.56 m

Merci voluminose

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	1700,00 W
Potenza in uscita:	Massimo 1500 W
Intervallo di frequenza:	120 - 18000 Hz
Misure:	Larghezza: 52 cm Profondità: 70 cm Altezza: 65 cm
Peso:	28,15 kg
Satellite speakers:	
Rated power:	300 W RMS
Program power:	450 W
Components:	25 cm woofer (10"), 2 cm horn (0.75")
Connection:	1 Speaker jack
Sensitivity:	99 dB
Maximum SPL:	121 dB
Impedance:	4 ohms
Crossover frequency:	2.5 kHz
Dispersion angle:	60° x 90°
Dimensions (H x W x D):	320 x 310 x 520 mm
Subwoofer:	
Rated power:	900 W RMS
Program power:	1200 W
Components:	45 cm woofer (18")
Inputs:	2 x combo jack XLR/6.3 mm
Through:	2 x XLR
Outputs:	2 x Speaker
Sensitivity:	101 dB
Maximum SPL:	127 dB
Impedance:	8 ohms
Dimensions (H x W x D):	650 x 520 x 700 mm
Amplifier:	
Total power output:	1500 W RMS
Power output to satellite speakers:	
Stereo 4 ohms:	2 x 560 W (RMS)
Stereo 8 ohms:	2 x 350 W (RMS)
Nominal power output subwoofer:	900 W RMS
Min. input sensitivity:	0.775 V
Control elements:	power switch, satellite level control, low/high equalizer, subwoofer level control, frequency crossover, limiter
LED indicators:	power and signal/limit per channel

Protection circuits:	short-circuit, DC voltage, thermal protection, softstart, opto limiter, subsonic filter
Equalizer:	
Tone control/channel:	
Treble:	±10 dB at 10 kHz
Bass:	±10 dB at 75 Hz
Active crossover:	
Crossover frequency:	50-250 Hz

Contenuto della confezione:
