

## OMNITRONIC ASS-1023 Active system

Powerful mobile column PA system, 600 W RMS

Art.n.: 11038852

GTIN:



**L'articolo non è più disponibile.**

### Features :

- Mobile column PA system with top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light - this system can be installed and setup in time
- Convinces with excellent speech reproduction and wide coverage
- Ideal for DJs, entertainers, small bands and various kinds of mobile PA applications
- Dual class D amplifier (400 W + 200 W RMS) with SMPS
- 2 x 25 cm bassreflex subwoofer
- Fullrange column speaker with 12 x 8 cm drivers
- Balanced 6.3 mm jack input and parallel XLR output
- Master level control with peak indication
- Adjustable crossover frequency for subwoofer
- Phase switchable for subwoofer
- Subwoofer with plywood enclosure
- Column speaker with MDF enclosure
- Scratch-resistant lacquer surface, impact-resistant steel grille and flange
- Delivery includes distance tube, speaker cable and power cable
- Castor set and wheel board available as accessory

### Logistica

### Dati tecnici :

|                    |                        |
|--------------------|------------------------|
| Peso:              | 36,70 kg               |
| Power supply:      | 115/230 V AC, 50/60 Hz |
| Power consumption: | 200 W (1/8 power)      |
| Power output sine: |                        |

|                      |                                               |
|----------------------|-----------------------------------------------|
| Subwoofer:           | 400 W RMS                                     |
| Satellite speaker:   | 200 W RMS                                     |
| Components:          |                                               |
| Subwoofer:           | 2 x 25 cm woofer (10")                        |
| Satellite speaker:   | 12 x 8 cm mid-high driver (12 x 3")           |
| Maximum SPL:         |                                               |
| Subwoofer:           | 120 dB                                        |
| Satellite speaker:   | 118 dB                                        |
| Frequency range:     |                                               |
| Subwoofer:           | 45-180 Hz                                     |
| Satellite speaker:   | 120-20000 Hz                                  |
| Crossover frequency: | 40-160 Hz                                     |
| Microphone input:    | combination XLR/6.3 mm jack, bal.             |
| Line input:          | combination XLR/6.3 mm jack, bal. and RCA L/R |
| Speaker output:      | 1 x speaker, 4 ohms                           |