

OMNITRONIC ASS-1023 Active system

Powerful mobile column PA system, 600 W RMS

Art.n.: 11038852

GTIN:



Features :

- Mobile column PA system with top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light - this system can be installed and setup in time
- Convinces with excellent speech reproduction and wide coverage
- Ideal for DJs, entertainers, small bands and various kinds of mobile PA applications
- Dual class D amplifier (400 W + 200 W RMS) with SMPS
- 2 x 25 cm bassreflex subwoofer
- Fullrange column speaker with 12 x 8 cm drivers
- Balanced 6.3 mm jack input and parallel XLR output
- Master level control with peak indication
- Adjustable crossover frequency for subwoofer
- Phase switchable for subwoofer
- Subwoofer with plywood enclosure
- Column speaker with MDF enclosure
- Scratch-resistant lacquer surface, impact-resistant steel grille and flange
- Delivery includes distance tube, speaker cable and power cable
- Castor set and wheel board available as accessory

Logistica

Dati tecnici :

| | |
|--------------------|------------------------|
| Peso: | 36,70 kg |
| Power supply: | 115/230 V AC, 50/60 Hz |
| Power consumption: | 200 W (1/8 power) |
| Power output sine: | |

| | |
|----------------------|---|
| Subwoofer: | 400 W RMS |
| Satellite speaker: | 200 W RMS |
| Components: | |
| Subwoofer: | 2 x 25 cm woofer (10") |
| Satellite speaker: | 12 x 8 cm mid-high driver (12 x 3") |
| Maximum SPL: | |
| Subwoofer: | 120 dB |
| Satellite speaker: | 118 dB |
| Frequency range: | |
| Subwoofer: | 45-180 Hz |
| Satellite speaker: | 120-20000 Hz |
| Crossover frequency: | 40-160 Hz |
| Microphone input: | combination XLR/6.3 mm jack, bal. |
| Line input: | combination XLR/6.3 mm jack, bal. and RCA L/R |
| Speaker output: | 1 x speaker, 4 ohms |

Contenuto della confezione:
