

OMNITRONIC PAS-212PRO-A 2-Way Top, active, DSP

Active 2-way PA speaker system with DSP

Art.n.: 11039445

GTIN: 4026397531275



L'articolo non è più disponibile.

Features :

- Active 2-way speaker system for touring applications and permanent installations
- Class D circuitry with switch-mode power supply and 800 watts peak power
- DSP with 5 EQ presets and status display window
- Rugged full-range top speaker qualified for suspended installation and flange for stand installation
- Rotatable constant directivity horn (asymmetrical) with coil driver
- 30 cm woofer in bassreflex cabinet provides powerful, dry bass
- Power, signal and limiter indication
- Adjustable line input, (XLR/6.3 mm jack and RCA)
- Adjustable microphone input (XLR/6.3 mm jack), switchable to line
- Line output (XLR) for linking further active speaker systems
- Optimized for combination with PAS subwoofers
- Impact-resistant steel grille with acoustic foam
- Trapezoidal, multilayered glued plywood housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended
- Suitable for car transport

Logistica

EAN / GTIN: 4026397531275

Peso : 19,15 kg

Lunghezza : 0.45 m

Larghezza : 0.42 m

Altezza : 0.68 m

Dati tecnici :

Alimentazione elettrica: 100-240 V AC, 50/60 Hz

Potenza totale installata: 110 W

Capacità di carico: Programma: 800W
Nominale: 400W RMS

Intervallo di frequenza:	55 - 20000 Hz
Altoparlante:	1 x 12" Woofer
Tipo di altoparlante:	Cassa compatta
Misure:	Larghezza: 35,5 cm Profondità: 33 cm Altezza: 60 cm
Peso:	17,20 kg
Components:	30 cm woofer (12"), 3.6 cm horn (1.4")
Input:	
Line:	Combination XLR/6.3 mm jack, RCA L/R
Mic:	Combination XLR/6.3 mm jack
Output:	
Line:	XLR
Sensitivity:	97 dB
Maximum SPL:	124 dB
Crossover frequency:	2 kHz
Dispersion angle:	50-100° x 55°
Dimensions (H x W x D):	600 x 355 x 330 mm