

## PSSO CSA-228A top, active, black

Pro active PA speaker system with biamp amplifier, 450 W

Art.n.: 11040815

GTIN: 4026397527643



**L'articolo non è più disponibile.**

### Features :

- Active full-range top speaker, qualified for suspension
- For permanent installations and touring purposes
- Class D biamp power amplifier (450 W)
- Efficient, light-weight switch mode power supply with energy saving mode
- Light-weight cabinet due to high-quality special plastic (15 kg only)
- Elegant housing design
- 2 x 20 cm (8") bass speaker and 3.5 cm (1.35") titanium compression horn driver
- 90° x 40° nominal coverage
- Balanced XLR input
- Speaker flange for mobile use included in the delivery
- PowerCon mains input
- Applications: as monitor, on a subwoofer or speaker stand, suspended
- Matching mounting brackets and flying hardware available as accessories

### Logistica

EAN / GTIN: 4026397527643

Peso : 18,60 kg

Lunghezza : 0.76 m

Larghezza : 0.42 m

Altezza : 0.40 m

### Dati tecnici :

|                          |                                        |
|--------------------------|----------------------------------------|
| Alimentazione elettrica: | 100-240 V AC, 50/60 Hz                 |
| Intervallo di frequenza: | 70 - 18000 Hz                          |
| Altoparlante:            | 2 x 8" Woofer                          |
| Tipo di altoparlante:    | Cassa compatta                         |
| Rated power:             | 450 W                                  |
| Components:              | HF: 3.5 cm (1.35"), LF: 2 x 20 cm (8") |

|                      |                                            |
|----------------------|--------------------------------------------|
| Crossover frequency: | 2.5 kHz                                    |
| Dispersion angle:    | 90° x 40°                                  |
| Maximum SPL:         | 119 dB                                     |
| Acoustic loading:    | Bassreflex                                 |
| Cabinet material:    | HIPS                                       |
| Amplifier:           | Class D                                    |
| THD:                 | <0.05 %                                    |
| S/N ratio:           | >80 dB                                     |
| Damping factor:      | >50                                        |
| Input sensitivity:   | 2 V                                        |
| Input impedance:     | 40 kohms/20 kohms (bal./unbal.)            |
| Signal input:        | XLR                                        |
| Power consumption:   | 550 W                                      |
| Protection circuits: | Limiter, overheat, overload, short-circuit |
| LED indicators:      | Power, clip                                |
| Weight:              | 16 kg                                      |