

PSSO K-215SE 2-Way Top 600W

PRO PA speaker, 15" woofer, 1.5" horn, 600 W RMS, 8 ohms

Art.n.: 11041109

GTIN: 4026397545401



L'articolo non è più disponibile.

Features :

- Rugged full-range top speaker, qualified for suspension and touring applications
 - Housing made of 15 mm/18 mm birch plywood
 - 38 cm (15") bass speaker with diecast aluminum basket
 - Rotatable constant directivity horn tweeter with titanium diaphragm
 - Horn exit 38 mm (1.5")
 - Voice coil 72 mm (2.8")
 - Premium custom-made drivers by European manufacturer CELTO Acoustique
 - Passive 2-way crossover
 - Bassreflex system
 - Parallel Neutrik Speakon connectors
 - Trapezoidal multi-functional housing with scratch-resistant lacquer surface
 - Impact-resistant steel grille with acoustic foam
 - Dual-angle-Flange for stand installation
 - Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
 - Driver di CELTO ACOUSTIQUE
 - Collegamento a innesto NEUTRIK installato
 - Realizzato in europa
- Dotazione della fornitura**
- 1 x testata, 1 x Manuale d'uso

Logistica

EAN / GTIN: 4026397545401

Peso : 32,45 kg

Lunghezza : 0.51 m

Larghezza : 0.49 m

Altezza : 0.79 m

Merci voluminose

Dati tecnici :

Capacità di carico:

Programma: 1200W

Nominale: 600W RMS

Intervallo di frequenza:	47 - 19000 Hz
Sensibilità:	99 dB (1W/1m)
Pressione acustica massima:	127 dB
Direzionalità:	80° x 50°
Impedenza:	8 Ohm
Collegamenti:	Ingresso: Altoparlante via 2 x SpeakON a 2 poli (F) versione da incasso
Frequenza di taglio:	1500 Hz
Altoparlante:	1 x 15" Woofer 1 x 1,35" Tromba
Tipo di altoparlante:	Cassa compatta
Uso del marchio:	Driver di CELTO ACOUSTIQUE Collegamento a innesto NEUTRIK installato
Misure:	Larghezza: 44,5 cm Profondità: 41,5 cm Altezza: 71 cm
Peso:	29,45 kg