

OMNITRONIC UHF-400 Wireless mic system

Complete 4-channel UHF microphone system

Art.n.: 13053510

GTIN: 4026397195330



L'articolo non è più disponibile.

Descrizione :

Ride on a musical wave!

Set yourself free, break the chains of tight confining cables and be happy wireless. With our OMNITRONIC UHF-400 wireless mic system you will get the one time opportunity. It convinces through a high level manufacture, its consolidated appearance and its classic simple design, which intentionally sets itself aside from nonessential squiggle. Equipped with 4 hand microphones in cardioid characteristic, with a fixed channel reception and transmitter unit. At the same time, the 4 channels can be used simultaneously at fixed frequencies. One thing is for sure, the UHF-400 invites you to go surfing on the radio waves.

Features :

- Set includes 483 mm receiver unit (19") and 4 hand-held microphones with integrated transmitter in a practical transport suitcase
- Receiver unit in a rugged metal housing
- Two removable rubber antennas (TNC connection)
- Operation with 4 fixed frequencies in the low-interference UHF band (790.000-814.000 MHz)
- Operation range up to 80 meters (with line-of-sight)
- 4 separate channels with controls for volume and squelch, LEDs for power supply and signal reception
- XLR output per channel and 6.3 mm jack for mixed signal
- Jack-jack cable included
- Operation of the receiving unit via supplied power unit
- Operation of the microphones via 2 x 1.5 V mignon batteries (type AA)
- Delivery includes 4 color caps to distinguish the microphones on stage
- Pocket transmitter with headset microphone can be ordered separately
- Rack installation, 1 U

Logistica

EAN / GTIN: 4026397195330

Peso : 6,20 kg

Lunghezza : 0.53 m

Larghezza : 0.31 m

Altezza : 0.14 m

- License-free and approved in Germany

Dati tecnici :

| | |
|----------------------------|---|
| Potenza totale installata: | 5,00 W |
| Banda di frequenza: | UHF |
| Misure: | Larghezza: 48,3 cm Profondità: 25 cm Altezza: 4,45 cm |
| Wireless receiver: | |
| System: | Non-diversity |
| Frequency stability: | ±0.002 % |
| Frequencies: | |
| Red: | UHF 796.700 MHz |
| Yellow: | UHF 804.750 MHz |
| Blue: | UHF 805.100 MHz |
| Gray: | UHF 808.975 MHz |
| S/N ratio: | >90 dB |
| Selectivity: | >80 dB |
| Dynamic range: | >80 dB |
| Modulation method: | FM |
| AF response: | 40-16000 Hz |
| Audio output: | 4 x XLR (channel), 1 x mono 6.3 mm jack (mixed out) |
| Power supply: | 13-18 V DC, 500 mA |
| Dimensions: | 483 x 250 x 44 mm |
| Weight: | 1 kg |
| Wireless microphone: | |
| RF power output: | 30 mW |
| Coverage: | 80 m (with line-of-sight) |
| Power supply: | 2 x 1.5 V Mignon batteries (type AA) |
| Current consumption: | approx. 55 mA |
| Battery life: | approx. 8-10 hours |
| Dimensions: | 50 x 260 mm |
| Weight: | 400 g |