

OMNITRONIC UHF-204 Wireless Mic System 863-865MHz

Complete 4-channel UHF PLL microphone system

Art.n.: 13063216

GTIN: 4026397478426



L'articolo non è più disponibile.

Features :

- 4-channel receiver unit and 4 hand-held microphones with UHF PLL technology
- Operation in the low-interference UHF band (863-865 MHz) with 4 fixed frequencies
- 4 separate channels with volume controls and LEDs for power supply, carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Jack cable included
- Microphones with mute switch and color caps for distinction on stage
- Matching pocket transmitters can be ordered separately
- Removable antennas (TNC connection)
- Receiver unit in a rugged metal housing
- Incl. mounting brackets for 483 mm rack installation
- License-free and approved in the EU
- Direttività: Cardioide
- UHF 863 - 865 MHz registrazione e gratuità in Europa
- Custodia per mixer
- Montaggio su rack (19") 48,3 cm possibile

Dotazione della fornitura

- 1 x microfono

Logistica

EAN / GTIN: 4026397478426

Peso : 4,65 kg

Lunghezza : 0.53 m

Larghezza : 0.29 m

Altezza : 0.12 m

Dati tecnici :

Tipo: Set senza fili completo

Potenza totale installata: 10,00 W

Tipo di capsula:	Dinamica
Direttività:	Cardioide
Intervallo di frequenza:	40 - 18000 Hz
Banda di frequenza:	UHF 863 - 865 MHz
Selezione frequenza:	Frequenze uniche
Interruttore:	Interruttore silenzioso; Interruttori di accensione/spegnimento
Struttura della custodia:	Custodia per mixer Montaggio su rack (19") 48,3 cm possibile
Misure:	Larghezza: 42 cm Profondità: 5 cm Altezza: 22 cm
Microfono	
Pila:	8 x Mignon (AA) (non in dotazione)
System:	Diversity, 4 channels
Carrier frequency:	863.010 MHz, 863.420 MHz, 864.300 MHz, 864.990 MHz
Coverage:	50 m (with line-of-sight)
RF power output:	10 mW
Modulation method:	F3F
S/N ratio:	>105 dB
Selectivity:	>80 dB
T.H.D.:	<0.5 % at 1 kHz
Audio outputs:	
Mic:	4 x XLR, bal.
Level/impedance:	400 mV, 2.2 kohms
Mic:	6.3 mm jack, unbal.
Level/impedance:	200 mV, 2.2 kohms
Power supply	
Receiver:	100-240 V AC, 50/60 Hz via supplied power unit
Dimensions, weight	
Receiver:	420 x 220 x 50 mm (L x W x H), 3 kg
Microphones:	50 x 265 mm (D x L), 280 g