



L'articolo non è più disponibile.

Features :

EUROLITE LED Pixel Pole 50cm

LED bar for pixel mapping applications

- LED bar with 16 or 32 pixels for video and pixel mapping applications via Art-Net
- Signal distribution via UTP cable
- Crea facilmente animazioni con MADRIX o qualsiasi altro software con supporto Art Net
- 16 potenti LED SMD 5050 3in1 TCL RGB (miscela di colori omogenea)
 LED controllabili singolarmente
- Miscela di colori in continuo; Dimmer elettronico
- Effetto stroboscopico
- 30 programmi di spettacolo integrati
- Controllabile via accessori; funzione master/slave
- With a beam angle of 180°
- Per campi di applicazione come, ad esempio,: Allestimenti per fiere e negozi; club/scuole di danza; palco

EUROLITE LED PSU-4A Artnet/DMX

Control unit for EUROLITE LED Pixel Poles

- Create sensational effects in conjunction with the decorative LED Pixel Poles
- Control via Art-Net/DMX
- For use with MADRIX or any other lighting control software supporting Art-Net
- Connections for 4 x 160 pixels
- Signal distribution via UTP cable
- Stand-alone operation possible with 30 built-in light programs
- Master/Slave for parallel operation of several devices

Logistica

- Comfortable addressing and setting via control panel with LC display
- RGB color mixture, dimmer and strobe function
- P-Con terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- Controllabile via stand-alone; Art-Net; DMX
- Già pre-programmato con LED PC-Control 512

OMNITRONIC CAT-5 Cavo 5m nero

Cavi dati o di rete

- OEM
- Made in Germany

OMNITRONIC CAT-5 Cavo 1 m nero

Cavi dati o di rete

- OEM

MADRIX KEY entry

MADRIX KEY + MADRIX 5 license "entry"

- Includes 1x MADRIX KEY and 1x MADRIX 5 License entry
- MADRIX 5 is a powerful, easy-to-use, and award-winning LED lighting control software
- Allows you to realize all kinds of different LED projects and lighting designs
- A normal PC/laptop can be used for professional LED control
- Activates output for up to 8x 512 DMX channels (4,096 DMX channels, or 8 DMX universes, for example) and up to 16,384 DVI voxels (a resolution of 128 x 128 pixels, for example)
- The license is activated via a USB dongle and can be used flexibly on different computers as needed
- Can be upgraded to higher licenses (up to MADRIX 5 KEY maximum)
- Online activation is initially required one time
- Only one MADRIX 5 License is possible per MADRIX KEY
- Only one MADRIX 5 KEY can be connected to the software
- Supports many industry protocols and communication standards for direct connection to your LEDs and LED controllers: Art-Net (I, II, 3, 4) (Unicast & Broadcast), DMX512, Philips Color Kinetics KiNET (V1 / V2), Philips Hue, SPI (via MADRIX NEBULA), Streaming ACN (sACN / E1.31) (Unicast & Multicast), ColourSmart Link, Colorlight A8, Colorlight 5A, Colorlight T9, DVI (VGA, HDMI, and more), Eurolite T9
- Even more options are available via converters or bridging tools
- Allows mapping in 2D (pixel mapping) as well as real, spatial 3D (voxel mapping)
- The software generates unique effects, visuals, and animations live and in real time
- No additional content is required
- Already includes a multitude of stock effects that are fully customizable (in speed, color, shape, direction, size, movement, position, brightness, and many more)
- Analyzes incoming audio signals for Sound2Light and Music2Light in real time (WDM or ASIO)
- TRI effect category for interactive performances
- New lighting scenes can easily be created in seconds
- Supports media server features also: Conveniently load and play back images, pictures, logos, and videos as well as live video signal capturing, screen capturing, scrolling text (ticker), and more
- Supports audio playback for videos
- Variety of options to combine visuals and graphical elements (layers, mix modes, filters, etc.)
- Clean and simple user interface with 2 themes (dark and light)
- DJ-/VJ-like operation with 2 decks (A/B) and a crossfader
- 256 x 256 Storage Places to organize and store effects
- 3 real-time previews to show your visual effects in advance (incl. 2D/3D, zoom, rotation)
- 2 DVI outputs
- Controls up to 4 color channels per pixel/voxel (1-channel, 2-channel, RGB, RGBW fixtures, for example)
- Freely configurable Cue List for automated playback of a show (incl. time, date, duration, etc.)
- Supports Time Code (Art-Net, MIDI, SMPTE, and System Time)

- Input, interoperability, and remote control available through industry standards: Art-Net (I, II, 3, 4), Blackmagic Design (DeckLink, Intensity, and more), C1TP, DMX512, GamePort, MA-Net 1 / MA-Net 2, MADRIX I/O, MIDI, NewTek NDI (Send & Receive), Remote HTTP (Web Server), Spout (Send & Receive), Streaming ACN (sACN / E1.31)
- Even more options are available via converters or bridging tools
- Accompanying Fixture Editor including large fixture library
- Comfortable patching features (incl. Matrix Generator, graphical Patch Editor with background image support, DVI Patch, CSV Fixture List Import, Fixture List Export, and more)
- Includes various other tools and features (Art-Net Time Code Sender, DMX Fader Tool, DMX Watcher, MIDI Watcher, Touch Screen window, backup system, scripting, mapping, scaling, etc.)
- Supports various 3rd-party interfaces via aforementioned standards as well as MADRIX hardware interfaces (sold separately)
- Minimum system requirements: 2.0 GHz dual-core CPU, OpenGL 2.1 graphics card (NVIDIA recommended), 2 GB RAM, 1 GB free harddisk space, 1280 x 768 screen resolution, network card, sound card, USB 2.0 (optimal system specifications will often be higher)
- Supported operating systems: Microsoft Windows 7 | 8 | 8.1 | 10 (64 bit only)
- Package contents: Beautiful, high-quality box including 1x MADRIX KEY, 1x USB flash drive incl. MADRIX 5 Software, 1x lanyard, and 1x quick start guide
- Software and installation instructions available in English, German, Spanish, French, and Simplified Chinese
- All user manuals are provided digitally and available in English
- User manuals also available at help.madrix.com
- Made in Germany
- Free software demo mode and more information available at www.madrix.com

Dati tecnici :

Peso:	6,34 kg
-------	---------

EUROLITE LED Pixel Pole 50cm

Alimentazione elettrica:	24V DC
Potenza totale installata:	2 W
Classe di protezione:	CL III
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite RJ-45 (F) versione da incasso
Tipo di LED:	16 x SMD 5050 3in1 TCL RGB (miscela di colori omogenea)
Attivazione:	Accessori; funzione master/slave
Angolazione del fascio di luce:	180°
Angolazione del fascio di luce (1/2 picco):	180°
Immagine:	16 px Passo di pixel 30 mm
Colore della custodia:	Argento
Collegamenti:	Segnale via 2 x RJ-45 (F) versione da incasso
Misure:	Lunghezza: 50 cm Profondità: 3,2 cm Altezza: 3,2 cm
Peso:	0,11 kg
Specifiche legali	

Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali

EUROLITE LED PSU-4A Artnet/DMX

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	200 W
Grado di protezione:	IP20
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite P-Con (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Canali DMX:	8
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso
Connessione di rete:	2x RJ-45 (F) versione da incasso
Attivazione:	Stand-alone; Art-Net; DMX
Pre-programmato con:	LED PC-Control 512
Colore della custodia:	Nero
Misure:	Larghezza: 21,5 cm Profondità: 28,5 cm Altezza: 8,5 cm
Peso:	2,57 kg
Serial connection:	yes
Art-Net control:	4 x 160 pixels

OMNITRONIC CAT-5 Cavo 5m nero

Struttura cavo:	CAT5
Lunghezza cavo:	5 m
Collegamento A:	1 x RJ-45 (M)
Collegamento B:	1 x RJ-45 (M)
Uso del marchio:	OEM
Colore:	Nero
Peso:	0,18 kg

OMNITRONIC CAT-5 Cavo 1 m nero

Struttura cavo:	CAT5
Lunghezza cavo:	1 m
Collegamento A:	1 x RJ-45 (M)
Collegamento B:	1 x RJ-45 (M)
Uso del marchio:	OEM
Colore:	Nero
Peso:	0,05 kg